

Certificate

Issue Date: November 24, 2022
Ref. Report No. ISL-22LR0199FCCIC

Product Name : Gateways
Main Model : BLG840FB4
Series Model : BLG840FB16; BLG40EB16
Brand : Fanstel
Applicant : Fanstel Corporation, Taipei
Address : 10F-10, No. 79, Sec. 1, Hsin Tai Wu Rd.,
Hsi-Chih, New Taipei City 221 Taiwan

We, **International Standards Laboratory Corp.**, hereby certify that:

The sample ISL received which bearing the trade name and model specified above has shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified. (refer to Test Report if any modifications were made for compliance). And Our laboratories is the accredited laboratories and are approved according to ISO/IEC 17025.

Standards:

FCC CFR Title 47 Part 15 Subpart B: Section 15.107 and 15.109
ANSI C63.4-2014
Industry Canada Interference-Causing Equipment Standard ICES-003 Issue 7: 2020
Class B

I attest to the accuracy of data and all measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

The determination of the test results is determined by customer agreement, regulations or standard document specifications.

The Laboratory evaluates measurement inaccuracies based on regulatory or standard document specifications and is listed in the report for reference. The quantitative project part judges the conformity of the test results based on the evaluation results of the standard cited uncertainty, and the qualitative project does not temporarily evaluate the measurement uncertainty.



Angus Chu / Sr. Manager

International Standards Laboratory Corp. LT Lab.

TEL: +886-3-263-8888 FAX: +886-3-263-8899

No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist., Tao Yuan City 325, Taiwan

TEST REPORT

of

CFR 47 Part 15 Subpart B Class B & Industry Canada Interference-Causing Equipment Standard ICES-003 Class B

Application Type: Supplier's Declaration of Conformity

Product: Gateways
Main Model: BLG840FB4
Series Model: BLG840FB16; BLG40EB16
Brand: Fanstel
Applicant: Fanstel Corporation, Taipei
Address: 10F-10, No. 79, Sec. 1, Hsin Tai Wu Rd.,
Hsi-Chih, New Taipei City 221 Taiwan

Test Performed by:



International Standards Laboratory Corp. LT Lab.

TEL: +886-3-263-8888 FAX: +886-3-263-8899

No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist., Tao Yuan City 325, Taiwan

Report No.: **ISL-22LR0199FCCIC**
Issue Date : **November 24, 2022**





Test results given in this report apply only to the specific sample(s) tested and are traceable to national or international standard through calibration of the equipment and evaluating measurement uncertainty herein. The uncertainty of the measurement does not include in consideration of the test result unless the customer required the determination of uncertainty via the agreement, regulation or standard document specification. This test report shall not be reproduced except in full, without the written approval of International Standards Laboratory Corp.

Contents of Report

| | | |
|-----|---|----|
| 1. | General | 1 |
| 1.1 | Certification of Accuracy of Test Data | 1 |
| 1.2 | Description of EUT | 2 |
| 1.3 | Description of test modes | 3 |
| 1.4 | Configuration of Tested System | 4 |
| 2. | Power Line Conducted Emissions..... | 5 |
| 2.1 | Test Setup and Procedure | 5 |
| 2.2 | Conduction Test Data: Configuration 1 | 7 |
| 2.3 | Test Setup Photo..... | 9 |
| 3. | Radiated Emissions | 11 |
| 3.1 | Test Setup and Procedure | 11 |
| 3.2 | Radiation Test Data: Configuration 1..... | 15 |
| 3.3 | Test Setup Photo..... | 19 |
| 4. | Appendix | 21 |
| 4.1 | Appendix A: (FCC)Warning Labels..... | 21 |
| 4.2 | Appendix B: (FCC)Warning Statement | 22 |
| 4.3 | Appendix C: (Canada ISED) Labelling and user manual requirements..... | 23 |
| 4.4 | Appendix D: Test Equipment | 24 |
| 4.5 | Appendix E: Uncertainty of Measurement..... | 25 |
| 4.6 | Appendix F: Photographs of EUT | 26 |

1. General

1.1 Certification of Accuracy of Test Data

| | |
|------------------------------|---|
| Standards: | FCC CFR Title 47 Part 15 Subpart B: Section 15.107 and 15.109 ANSI C63.4-2014 Industry Canada Interference-Causing Equipment Standard ICES-003 Issue 7: 2020 Class B |
| Equipment Tested: | Gateways |
| Main Model: | BLG840FB4 |
| Series Model: | BLG840FB16; BLG40EB16 |
| Brand: | Fanstel |
| Applicant: | Fanstel Corporation, Taipei |
| Sample received Date: | November 9, 2022 |
| Final test Date: | refer to the date of test data |
| Test Site: | Chamber 19; Chamber 19; Conduction 02 |
| Test Distance: | 3m; 3m (above 1GHz) |
| Temperature: | refer to each site test data |
| Humidity: | refer to each site test data |
| Input power: | Conduction input power: AC 120 V / 60 Hz Radiation input power: AC 120 V / 60 Hz |
| Test Result: | PASS |
| Report Engineer: | Gigi Yeh |
| Test Engineer: |  Jason Chao |
| Approved By: |  Jerry Liu / Assistant Manager |

1.2 Description of EUT

EUT

| | |
|-------------------|--|
| Product Name: | Gateways |
| Brand Name: | Fanstel |
| Model Name: | BLG840FB4; BLG840FB16; BLG40EB16 |
| Model Difference: | Different market |
| Power Supply: | Model: GAT-0501000U AC Input: 100-240V~ 0.4A,50/60Hz DC Output: 5V, 1A |
| Micro USB port | 1 |
| SIM slot | 1 |
| Antenna port | 2 |

1.3 Description of test modes

| Applicable standard | | FCC 15B, ICES-003 | | |
|---------------------|---|---|---|---|
| Test Configuration | | Config 1 | Config 2 | Config 3 |
| | | EUT + Smart mobile phone+Wideband Radio Communication tester | EUT + Smart mobile phone+Wideband Radio Communication tester | EUT + Smart mobile phone+Wideband Radio Communication tester |
| Operation mode | | LTE and BLE link(BLG40EB16) | LTE and BLE link(BLG840FB16) | LTE and BLE link(BLG840FB4) |
| No. | Description | | | |
| 1 | Radiated emission(30M~1GHz)(above 1GHz) | Measured | Pretest | Pretest |
| 3 | Conducted emission (AC Power) | Measured | N/A | N/A |

1.4 Configuration of Tested System

Fig. 1-1 Configuration

Config. 1




Table 1-1 Support Equipment Used in Tested System

| Item | Equipment | Mrf/Brand | Model name | Series No | Data Cable | Power Cable |
|------|-------------------------------------|-----------|------------|----------------------|------------|--------------------|
| 1 | Wideband Radio Communication tester | R&S | CMW500 | 1201.002K50108793-JG | N/A | Non-Shielded /1.8m |
| 2 | Smart mobile phone | hTC | PL99110 | N/A | N/A | N/A |

I/O Cable Condition of EUT and Support Units

| Description | Path | Cable Length | Cable Type | Connector Type |
|-----------------|--|--------------|------------|----------------|
| USB power cable | Adaptor USB port to EUT micro USB port | 2m | Shielded | Metal |


Note: All the above equipment/cables were placed in worse case positions to maximize emission signals during emission test.

Grounding: Grounding was in accordance with the manufacturer's requirements and conditions for the intended use.

2. Power Line Conducted Emissions

2.1 Test Setup and Procedure

2.1.1 Test Setup



2.1.2 Test Procedure

The measurements are performed in a shielded room test site. The EUT was placed on non-conduction 1.0m x 1.5m table, which is 0.8 meters above an earth-grounded.

Power to the EUT was provided through the LISN which has the Impedance (50ohm/50uH) vs. Frequency Characteristic in accordance with the standard. Power to the LISNs were filtered to eliminate ambient signal interference and these filters were bonded to the ground plane. Peripheral equipment required to provide a functional system (support equipment) for EUT testing was powered from the second LISN through a ganged, metal power outlet box which is bonded to the ground plane at the LISN.

The interconnecting cables were arranged and moved to get the maximum measurement. Both the line of power cord, hot and neutral, were measured. All of the interface cables were manipulated according to ANSI C63.4 requirements.

The highest emissions were analyzed in details by operating the spectrum analyzer in fixed tuned mode to determine the nature of the emissions and to provide information which could be useful in reducing their amplitude.

2.1.3 EMI Receiver/Spectrum Analyzer Configuration (for the frequencies tested)

| | |
|-----------------------|---------------------------|
| Frequency Range: | 150kHz~30MHz |
| Detector Function: | Quasi-Peak / Average Mode |
| Resolution Bandwidth: | 9kHz |

2.1.4 Limit

Conducted emissions limits of Class A equipment. (AC mains power terminals):

| Frequency range (MHz) | Quasi-peak (dB μ V) | Average (dB μ V) |
|--------------------------|----------------------------|-------------------------|
| 0.15-0.50 | 79 | 66 |
| 0.50-5.0 | 73 | 60 |
| 5.0-30 | 73 | 60 |

Note 1: Conducted emissions limits of FCC CFR Title 47 Part 15 Subpart B & Industry Canada Interference-Causing Equipment Standard ICES-003 are same.

Note2: The more stringent limit applies at transition frequencies.

Conducted emissions limits of Class B equipment. (AC mains power terminals):

| Frequency range (MHz) | Quasi-peak (dB μ V) | Average (dB μ V) |
|--|----------------------------|-------------------------|
| 0.15-0.50 | 66 to 56* | 56-46* |
| 0.50-5.0 | 56 | 46 |
| 5.0-30 | 60 | 50 |
| *The limit level in dB μ V decreases linearly with the logarithm of frequency. | | |

Note 1: Conducted emissions limits of FCC CFR Title 47 Part 15 Subpart B & Industry Canada Interference-Causing Equipment Standard ICES-003 are same.

Note2: The more stringent limit applies at transition frequencies.

2.2 Conduction Test Data: Configuration 1

- Line



Address: No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
Tao Yuan City 325, Taiwan.
Tel: 03-2638888


Conducted Emission Measurement

Date: 2022/11/10

operator: Jeff Liang

Temperature: 23 °C

Humidity: 54 %



Site: Conduction 02

Phase: L1

| No. | Frequency (MHz) | QP_R (dBuV) | AVG_R (dBuV) | Correct Factor (dB) | QP Emission (dBuV) | QP Limit (dBuV) | QP Margin (dB) | AVG Emission (dBuV) | AVG Limit (dBuV) | AVG Margin (dB) |
|-----|--------------------|----------------|-----------------|---------------------------|--------------------------|-----------------------|----------------------|---------------------------|------------------------|-----------------------|
| 1 | 0.154 | 27.25 | 11.50 | 9.67 | 36.92 | 65.78 | -28.86 | 21.17 | 55.78 | -34.61 |
| 2 | 0.210 | 25.17 | 11.39 | 9.66 | 34.83 | 63.21 | -28.38 | 21.05 | 53.21 | -32.16 |
| 3 | 0.258 | 23.63 | 10.85 | 9.67 | 33.30 | 61.50 | -28.20 | 20.52 | 51.50 | -30.98 |
| 4 | 0.294 | 22.72 | 11.06 | 9.67 | 32.39 | 60.41 | -28.02 | 20.73 | 50.41 | -29.68 |
| 5 | 0.350 | 20.59 | 11.42 | 9.67 | 30.26 | 58.96 | -28.70 | 21.09 | 48.96 | -27.87 |
| 6 | 0.530 | 25.05 | 16.99 | 9.68 | 34.73 | 56.00 | -21.27 | 26.67 | 46.00 | -19.33 |

Note:

Margin = QP/AVG Emission - Limit

QP/AVG Emission = QP_R/AVG_R + Correct Factor

Correct Factor = LISN Loss + Cable Loss

A margin of -8dB means that the emission is 8dB below the limit

The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.

If peak data can pass, it will be shown in "QP/AVG Correct" column, if not, QP/AVG data will instead.

- Neutral



Address: No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
Tao Yuan City 325, Taiwan.
Tel: 03-2638888


Conducted Emission Measurement

Date: 2022/11/10

operator: Jeff Liang

Temperature: 23 °C

Humidity: 54 %



Site: Conduction 02

Phase: N

| No. | Frequency (MHz) | QP_R (dBuV) | AVG_R (dBuV) | Correct Factor (dB) | QP Emission (dBuV) | QP Limit (dBuV) | QP Margin (dB) | AVG Emission (dBuV) | AVG Limit (dBuV) | AVG Margin (dB) |
|-----|--------------------|----------------|-----------------|---------------------------|--------------------------|-----------------------|----------------------|---------------------------|------------------------|-----------------------|
| 1 | 0.178 | 25.98 | 7.95 | 9.66 | 35.64 | 64.58 | -28.94 | 17.61 | 54.58 | -36.97 |
| 2 | 0.226 | 24.30 | 6.81 | 9.67 | 33.97 | 62.60 | -28.63 | 16.48 | 52.60 | -36.12 |
| 3 | 0.262 | 22.94 | 6.46 | 9.67 | 32.61 | 61.37 | -28.76 | 16.13 | 51.37 | -35.24 |
| 4 | 0.278 | 22.19 | 6.45 | 9.67 | 31.86 | 60.88 | -29.02 | 16.12 | 50.88 | -34.76 |
| 5 | 0.326 | 20.58 | 6.07 | 9.66 | 30.24 | 59.55 | -29.31 | 15.73 | 49.55 | -33.82 |
| 6 | 0.526 | 19.13 | 12.89 | 9.67 | 28.80 | 56.00 | -27.20 | 22.56 | 46.00 | -23.44 |

Note:

Margin = QP/AVG Emission - Limit

QP/AVG Emission = QP_R/AVG_R + Correct Factor

Correct Factor = LISN Loss + Cable Loss

A margin of -8dB means that the emission is 8dB below the limit

The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.


If peak data can pass, it will be shown in "QP/AVG Correct" column, if not, QP/AVG data will instead.

2.3 Test Setup Photo

Front View






Back View



3. Radiated Emissions

3.1 Test Setup and Procedure

3.1.1 Test Setup



The 3dB beam width of the horn antenna used for the test is as shown in the table below.
 1GHz~18GHz

| Frequency GHz | E-plane | H-plane | $\theta_{3dB}(\text{min})$ | d= 3 m |
|---------------|---------|---------|----------------------------|--------|
| | | | | w (m) |
| 1 | 88° | 147° | 88° | 5.79 |
| 2 | 68° | 119° | 68° | 4.04 |
| 3 | 73° | 92° | 73° | 4.44 |
| 4 | 70° | 89° | 70° | 4.20 |
| 5 | 55° | 60° | 55° | 3.12 |
| 6 | 63° | 62° | 62° | 3.60 |
| 7 | 48° | 49° | 48° | 2.67 |
| 8 | 39° | 46° | 39° | 2.12 |
| 9 | 32° | 42° | 32° | 1.72 |
| 10 | 30° | 39° | 30° | 1.61 |
| 11 | 32° | 35° | 32° | 1.72 |
| 12 | 35° | 32° | 35° | 1.89 |
| 13 | 34° | 31° | 31° | 1.66 |
| 14 | 32° | 27° | 27° | 1.44 |
| 15 | 36° | 26° | 26° | 1.39 |
| 16 | 40° | 28° | 28° | 1.50 |
| 17 | 43° | 26° | 26° | 1.39 |
| 18 | 41° | 22° | 22° | 1.17 |

18 GHz~26.5 GHz

| Frequency GHz | E-plane | H-plane | $\theta_{3dB}(\text{min})$ | d= 1 m | d= 3 m |
|---------------|---------|---------|----------------------------|--------|--------|
| | | | | w (m) | w (m) |
| 18 | 11.4° | 12.7° | 11.4° | 0.199 | 0.598 |
| 19 | 10.9° | 12.4° | 10.9° | 0.190 | 0.572 |
| 20 | 10.8° | 12.4° | 10.8° | 0.189 | 0.567 |
| 21 | 9.8° | 12° | 9.8° | 0.171 | 0.514 |
| 22 | 9.7° | 11° | 9.7° | 0.169 | 0.509 |
| 23 | 10° | 11.8° | 10° | 0.174 | 0.524 |
| 24 | 9° | 11° | 9° | 0.157 | 0.472 |
| 25 | 10° | 12.3° | 10° | 0.174 | 0.524 |
| 26 | 9.9° | 11.1° | 9.9° | 0.173 | 0.519 |
| 26.5 | 9.4° | 11.3° | 9.4° | 0.164 | 0.493 |

26 GHz~40 GHz

| Frequency GHz | E-plane | H-plane | $\theta_{3dB}(\text{min})$ | d= 1 m | d= 3 m |
|---------------|---------|---------|----------------------------|--------|--------|
| | | | | w (m) | w (m) |
| 26 | 12° | 12.2° | 12° | 0.210 | 0.631 |
| 27 | 13° | 10.5° | 10.5° | 0.184 | 0.551 |
| 28 | 13.2° | 12.3° | 12.3° | 0.216 | 0.647 |
| 29 | 11.5° | 12.8° | 11.5° | 0.201 | 0.604 |
| 30 | 12° | 8° | 8° | 0.140 | 0.420 |
| 31 | 11.5° | 10.1° | 10.1° | 0.177 | 0.530 |
| 32 | 11.8° | 10° | 10° | 0.175 | 0.525 |
| 33 | 11.8° | 9.5° | 9.5° | 0.166 | 0.499 |
| 34 | 11.6° | 10° | 10° | 0.175 | 0.525 |
| 35 | 10.9° | 9.8° | 9.8° | 0.171 | 0.514 |

| | | | | | |
|----|-------|-------|-------|-------|-------|
| 36 | 11.8° | 8.6° | 8.6° | 0.150 | 0.451 |
| 37 | 12.9° | 10.5° | 10.5° | 0.184 | 0.551 |
| 38 | 12° | 10.3° | 10.3° | 0.180 | 0.541 |
| 39 | 11.8° | 9.8° | 9.8° | 0.171 | 0.514 |
| 40 | 12.5° | 11.2° | 11.2° | 0.196 | 0.588 |

3.1.2 Test Procedure

The radiated emissions test will then be repeated on the chamber to measure the amplitudes accurately and without the multiple reflections existing in the shielded room. The EUT and support equipment are set up on the turntable of one of 10 meter chamber. Desktop EUT are set up on a wooden stand 0.8 meter above the ground or floor-standing arrangement shall be placed on the horizontal ground reference plane. The test volume for a height of up to 30 cm may be obstructed by absorber placed on the ground plane.

For the initial measurements, the receiving antenna is varied from 1-4 meter height and is changed in the vertical plane from vertical to horizontal polarization at each frequency. The highest emissions between 30 MHz to 1000 MHz were analyzed in details by operating the spectrum analyzer and/or EMI receiver in quasi-peak mode to determine the precise amplitude of the emissions. The highest emissions between 1 GHz to 40 GHz were analyzed in details by operating the spectrum analyzer in peak and average mode to determine the precise amplitude of the emissions.

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the antenna in the cone of radiation from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response. At the highest amplitudes observed, the EUT is rotated in the horizontal plane while changing the antenna polarization in the vertical plane to maximize the reading. The interconnecting cables were arranged and moved to get the maximum measurement. Once the maximum reading is obtained, the antenna elevation and polarization will be varied between specified limits to maximize the readings. All of the interface cables were manipulated according to ANSI C63.4 requirements.

The highest internal source of the EUT is defined as the highest frequency generated or used within the EUT or on which the EUT operates or tunes. If the highest frequency of the internal sources of the EUT is less than 108 MHz, the measurement shall only be made up to 1 GHz. If the highest frequency of the internal sources of the EUT is between 108 MHz and 500 MHz, the measurement shall only be made up to 2 GHz. If the highest frequency of the internal sources of the EUT is between 500 MHz and 1 GHz, the measurement shall only be made up to 5 GHz. If the highest frequency of the internal sources of the EUT is above 1 GHz, the measurement shall be made up to 5 times the highest frequency or 40 GHz, whichever is less.

3.1.3 Spectrum Analyzer Configuration (for the frequencies tested)

| | |
|-----------------------|-----------------|
| Frequency Range: | 30MHz--1000MHz |
| Detector Function: | Quasi-Peak Mode |
| Resolution Bandwidth: | 120kHz |

| | |
|-----------------------|-------------------|
| Frequency Range: | Above 1000MHz |
| Detector Function: | Peak/Average Mode |
| Resolution Bandwidth: | 1MHz |

3.1.4 Limit

Radiated emissions limits of Class A equipment. (30 MHz to 1 GHz)

| Frequency range (MHz) | FCC Part 15 Subpart B 15.109(g) | ICES-003 |
|-----------------------|--|--|
| | at 10 m distance Quasi-peak (dB μ V/m) | at 10 m distance Quasi-peak (dB μ V/m) |
| 30-88 | 40 | 40.0 |
| 88-216 | 40 | 43.5 |
| 216-230 | 40 | 46.4 |
| 230-960 | 47 | 47.0 |
| 960-1000 | 47 | 49.5 |

Note 1: The test limit in this report is based on FCC CFR Title 47 Part 15 Subpart B 15.109(g).

Note 2: The more stringent limit applies at transition frequencies.

Note 3: Test data in this report has been taken against the FCC CFR Title 47 Part 15 Subpart B 15.109(g) limit as it is the most stringent limit. By complying with the more restrictive Part 15 Subpart B 15.109(g) limit compliance with the Industry Canada Interference-Causing Equipment Standard ICES-003 limit is also demonstrated.

Radiated emission limits of Class A equipment at 3 m distance (above 1 GHz)

| Frequency range (GHz) | Average dB(μ V/m) | Peak dB(μ V/m) |
|-----------------------|------------------------|---------------------|
| 1 – 40G | 60 | 80 |

Note 1: Radiated emissions limits of FCC CFR Title 47 Part 15 Subpart B & Industry Canada Interference-Causing Equipment Standard ICES-003 are same.

Radiated emissions limits of Class B equipment. (30 MHz to 1 GHz)

| Frequency range (MHz) | FCC Part 15 Subpart B 15.109(a) | ICES-003 |
|-----------------------|---|---|
| | at 3 m distance Quasi-peak (dB μ V/m) | at 3 m distance Quasi-peak (dB μ V/m) |
| 30-88 | 40 | 40 |
| 88-216 | 43.5 | 43.5 |
| 216-230 | 46 | 46 |
| 230-960 | 46 | 47 |
| 960-1000 | 54 | 54 |

Note 1: The test limit in this report is based on FCC CFR Title 47 Part 15 Subpart B 15.109(a).

Note 2: The more stringent limit applies at transition frequencies.

Note 3: Test data in this report has been taken against the FCC CFR Title 47 Part 15 Subpart B 15.109(a) limit as it is the most stringent limit. By complying with the more restrictive Part 15 Subpart B 15.109(a) limit compliance with the Industry Canada Interference-Causing Equipment Standard ICES-003 limit is also demonstrated.

Radiated emission limits of Class B equipment at 3 m distance (above 1 GHz)


| Frequency range (GHz) | Average dB(μ V/m) | Peak dB(μ V/m) |
|-----------------------|------------------------|---------------------|
| 1 – 40G | 54 | 74 |

Note 1: Radiated emissions limits of FCC CFR Title 47 Part 15 Subpart B & Industry Canada Interference-Causing Equipment Standard ICES-003 are same.

3.2 Radiation Test Data: Configuration 1 - Radiated Emissions (Horizontal)



International Standard Laboratory Corp.
 Company Address: No. 120, Lane 180, Hsin Ho Rd.
 Lung-Tan Dist., Tao Yuan City 325, Taiwan
 Tel: (03) 2638888 ; Fax: (03) 2638899
 Web: www.isl.com.tw



Condition: FCC CLASS B 3M PK 3m HORIZONTAL
 Site : Chamber 19

Operator : Jason
 Temp : 23
 Hum : 55

| | Freq | Read | Factor | Level | Limit | Over | Remark | Pol/Phase |
|---|--------|-------|--------|--------|--------|--------|--------|------------|
| | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | |
| 1 | 127.97 | 38.66 | -7.40 | 31.26 | 43.50 | -12.24 | Peak | HORIZONTAL |
| 2 | 320.03 | 43.62 | -3.98 | 39.64 | 46.00 | -6.36 | Peak | HORIZONTAL |
| 3 | 376.29 | 43.36 | -3.25 | 40.11 | 46.00 | -5.89 | Peak | HORIZONTAL |
| 4 | 527.61 | 39.50 | -0.46 | 39.04 | 46.00 | -6.96 | Peak | HORIZONTAL |
| 5 | 568.35 | 39.65 | 0.24 | 39.89 | 46.00 | -6.11 | Peak | HORIZONTAL |
| 6 | 647.89 | 34.89 | 1.96 | 36.85 | 46.00 | -9.15 | Peak | HORIZONTAL |

- 1 -

* Note:

Margin = Level - Limit Line


Level = Read Level + Factor

Antenna Distance: 3 meters

If the peak measured value meets the QP limit, The QP value is inherently compliant.



International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Tel: (03) 2638888 ; Fax: (03) 2638899
Web: www.isl.com.tw



Condition: FCC CLASS B 3M PK 3m HORIZONTAL
Site : Chamber 19

Operator : Jason
Temp : 23
Hum : 55

| | Freq | Read | Factor | Level | Limit | Over | Remark | Pol/Phase |
|---|---------|-------|--------|--------|--------|--------|--------|------------|
| | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | |
| 1 | 1750.00 | 55.14 | -13.76 | 41.38 | 74.00 | -32.62 | Peak | HORIZONTAL |
| 2 | 3150.00 | 50.28 | -9.97 | 40.31 | 74.00 | -33.69 | Peak | HORIZONTAL |
| 3 | 5925.00 | 47.92 | -3.90 | 44.02 | 74.00 | -29.98 | Peak | HORIZONTAL |
| 4 | 6800.00 | 47.86 | -3.12 | 44.74 | 74.00 | -29.26 | Peak | HORIZONTAL |
| 5 | 7875.00 | 48.16 | -2.46 | 45.70 | 74.00 | -28.30 | Peak | HORIZONTAL |
| 6 | 8975.00 | 46.70 | -0.30 | 46.40 | 74.00 | -27.60 | Peak | HORIZONTAL |

- 1 -

* Note:

Margin = Level - Limit Line

Level = Read Level + Factor


Antenna Distance: 3 meters

If the peak measured value meets the Average limit, The Average value is inherently compliant.

-Radiated Emissions (Vertical)



International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Tel: (03) 2638888 ; Fax: (03) 2638899
Web: www.isl.com.tw



Condition: FCC CLASS B 3M PK 3m VERTICAL
Site : Chamber 19

Operator : Jason
Temp : 23
Hum : 55

| | Freq | Read Level | Factor | Level | Limit Line | Over Limit | Remark | Pol/Phase |
|---|--------|------------|--------|--------|------------|------------|--------|-----------|
| | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | |
| 1 | 31.94 | 42.76 | -7.58 | 35.18 | 40.00 | -4.82 | QP | VERTICAL |
| 2 | 50.37 | 43.42 | -5.53 | 37.89 | 40.00 | -2.11 | Peak | VERTICAL |
| 3 | 95.96 | 47.39 | -11.15 | 36.24 | 43.50 | -7.26 | Peak | VERTICAL |
| 4 | 106.63 | 46.51 | -9.41 | 37.10 | 43.50 | -6.40 | Peak | VERTICAL |
| 5 | 335.55 | 42.35 | -3.66 | 38.69 | 46.00 | -7.31 | Peak | VERTICAL |
| 6 | 352.04 | 42.98 | -3.71 | 39.27 | 46.00 | -6.73 | Peak | VERTICAL |

- 1 -

* Note:

Margin = Level - Limit Line


Level = Read Level + Factor

Antenna Distance: 3 meters

If the peak measured value meets the QP limit, The QP value is inherently compliant.



International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Tel: (03) 2638888 ; Fax: (03) 2638899
Web: www.isl.com.tw



Condition: FCC CLASS B 3M PK 3m VERTICAL
Site : Chamber 19

Operator : Jason
Temp : 23
Hum : 55

| | Freq | Read Level | Factor | Level | Limit Line | Over Limit | Remark | Pol/Phase |
|---|---------|------------|--------|--------|------------|------------|--------|-----------|
| | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | |
| 1 | 2825.00 | 51.43 | -10.85 | 40.58 | 74.00 | -33.42 | Peak | VERTICAL |
| 2 | 3550.00 | 49.83 | -9.09 | 40.74 | 74.00 | -33.26 | Peak | VERTICAL |
| 3 | 4075.00 | 49.91 | -8.68 | 41.23 | 74.00 | -32.77 | Peak | VERTICAL |
| 4 | 5800.00 | 48.05 | -4.05 | 44.00 | 74.00 | -30.00 | Peak | VERTICAL |
| 5 | 6375.00 | 47.46 | -2.89 | 44.57 | 74.00 | -29.43 | Peak | VERTICAL |
| 6 | 7225.00 | 48.43 | -3.15 | 45.28 | 74.00 | -28.72 | Peak | VERTICAL |

- 1 -

* Note:

Margin = Level - Limit Line


Level = Read Level + Factor

Antenna Distance: 3 meters


If the peak measured value meets the Average limit, The Average value is inherently compliant.

3.3 Test Setup Photo


Front View (30MHz~1GHz)




Back View (30MHz~1GHz)



Front View (above 1GHz)



Back View (above 1GHz)



4. Appendix

4.1 Appendix A: (FCC)Warning Labels

Label Requirements

A Class B digital device subject to authorization under Supplier's Declaration of Conformity of FCC shall carry a label which includes the following statement:

*** * * W A R N I N G * * ***

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Devices subject to authorization under Supplier's Declaration of Conformity may be labeled with FCC logo on a voluntary basis as a visual indication that the product complies with the applicable FCC requirements

The sample label shown shall be permanently affixed at a conspicuous location on the device and be readily visible to the user at the time of purchase.

When the device is so small or for such use that it is impracticable to label it with the statement specified under (§15.19 Labeling requirements) paragraph (a) of this section in a font that is four-point or larger, and the device does not have a display that can show electronic labeling, then the information required by this paragraph shall be placed in the user manual and must also either be placed on the device packaging or on a removable label attached to the device.

4.2 Appendix B: (FCC)Warning Statement

Statement Requirements

The operators' manual for a Class B digital device shall contain the following statements or their equivalent:

* * * W A R N I N G * * *

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Notice: The changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equivalent.

* * * * *

If the EUT was tested with special shielded cables the operator's manual for such product shall also contain the following statements or their equivalent:

Shielded interface cables and/or AC power cord, if any, must be used in order to comply with the emission limits.

4.3 Appendix C: (Canada ISED) Labelling and user manual requirements

The requirements specified in ICES-Gen shall apply. An example ISED compliance label, to be placed on each unit of an equipment model (or in the user manual, if allowed), is given below:

CAN ICES-003(*) / NMB-003(*)

* Insert either “A” or “B”, but not both, to identify the applicable Class of the device used for compliance verification.

The above label is only an example. The specific format is left to the manufacturer to decide, as long as the label includes the required information, in accordance with ICES-Gen.

4.4 Appendix D: Test Equipment

4.4.1 Test Equipment List

| Location | Equipment Name | Brand | Model | S/N | Last Cal. Date | Next Cal. Date |
|---------------|-----------------------------|---------------|---------------|-----------------|----------------|----------------|
| Conduction 02 | EMI Receiver 14 | ROHDE&SCHWARZ | ESCI | 101034 | 05/25/2022 | 05/25/2023 |
| Conduction 02 | Conduction 02-1 Cable | WOKEN | CFD 300-NL | Conduction 02-1 | 10/11/2022 | 10/11/2023 |
| Conduction 02 | LISN 26 | R&S | ENV216 | 102378 | 12/03/2021 | 12/03/2022 |
| Conduction 02 | LISN 21 | R&S | ENV216 | 101476 | 07/20/2022 | 07/20/2023 |
| Conduction 02 | ISN T4 07 | Teseq GmbH | ISN T400A | 30449 | 07/28/2022 | 07/28/2023 |
| Conduction 02 | ISN T8 10 | TESEQ | ISN T800 | 42773 | 08/05/2022 | 08/05/2023 |
| Conduction 02 | ISN T8 CAT6A 01 | SCHWARZBECK | NTFM 8158 | 8158 0123 | 01/25/2022 | 01/25/2023 |
| Conduction 02 | CDN ISN ST08A 1 | Teseq GmbH | CDN ISN ST08A | 43352 | 10/04/2022 | 10/04/2023 |
| Conduction 02 | Capacitive Voltage Probe 01 | SCHAFFNER | CVP 2200A | 18711 | 02/23/2022 | 02/23/2023 |
| Conduction 02 | Current Probe | SCHAFFNER | SMZ 11 | 18030 | 02/23/2022 | 02/23/2023 |

| Location Conducted | Equipment Name | Brand | Model | S/N | Last Cal. Date | Next Cal. Date |
|--------------------|----------------------------|----------------------|--|---------------------|----------------|----------------|
| Chamber 19 | Spectrum analyzer | R&S | FSV40 | 101919 | 08/17/2022 | 08/17/2023 |
| Chamber 19 | EMI Receiver | R&S | ESR3 | 102461 | 05/10/2022 | 05/10/2023 |
| Chamber 19 | Loop Antenna | EM | EM-6879 | 271 | 10/05/2022 | 10/05/2023 |
| Chamber 19 | Bilog Antenna (30MHz-1GHz) | Schwarzbeck | VULB9168 w 6dB Att. | 9168-736 | 03/09/2022 | 03/09/2023 |
| Chamber 19 | Horn antenna (1GHz-18GHz) | ETS | 3117 | 00218718 | 10/12/2022 | 10/12/2023 |
| Chamber 19 | Horn antenna (18GHz-26GHz) | Com-power | AH-826 | 081001 | 11/30/2021 | 11/30/2022 |
| Chamber 19 | Horn antenna (26GHz-40GHz) | Com-power | AH-640 | 100A | 03/18/2022 | 03/18/2023 |
| Chamber 19 | Preamplifier (9kHz-1GHz) | HP | 8447F | 3113A04621 | 06/24/2022 | 06/24/2023 |
| Chamber 19 | Preamplifier (1GHz-26GHz) | EM | EM01M26G | 060681 | 05/12/2022 | 05/12/2023 |
| Chamber 19 | Preamplifier (26GHz-40GHz) | MITEQ | JS4-26004000-27-5A | 818471 | 05/12/2022 | 05/12/2023 |
| Chamber 19 | RF Cable (100kHz-26.5GHz) | Huber Suhner & Woken | Sucoflex 104A & 18GHz SMA(M)-SM A(M)-10M | MY817/4A & 20200525 | 12/23/2021 | 12/23/2022 |
| Chamber 19 | RF Cable (18GHz-40GHz) | HUBER SUHNER | Sucoflex 102 | 27963/2&37421/2 | 11/17/2021 | 11/17/2022 |
| Chamber 19 | Signal Generator | Anritsu | MG3692A | 20311 | 12/28/2021 | 12/28/2022 |
| Chamber 19 | Test Software | Audix | E3 Ver:6.120203b | N/A | N/A | N/A |

4.4.2 Software for Controlling Spectrum/Receiver and Calculating Test Data

| Site | Filename | Version |
|----------------------|----------|----------|
| Conduction/Radiation | EZ EMC | ISL-03A2 |

4.5 Appendix E: Uncertainty of Measurement

The laboratory measurement uncertainty accordance with refers to CISPR 16-4-2. If U_{lab} is less than or equal to U_{cisp} in Table 1, then the test report may either state the value of U_{lab} or state that U_{lab} is less than U_{cisp} .

The coverage factor $k = 2$ yields approximately a 95 % level of confidence.

<Conduction 02>

AMN: $\pm 2.90\text{dB}$

ISN T2: $\pm 3.18\text{dB}$

ISN T4: $\pm 3.19\text{dB}$

ISN T8: $\pm 3.19\text{dB}$

ISN-T8(Cat 6a_10Gbps): $\pm 3.20\text{dB}$

CVP: $\pm 3.62\text{dB}$

CP: $\pm 2.88\text{dB}$

<Chamber 19 (3m)>

30MHz~1000MHz: $\pm 4.22\text{ dB}$

1GHz~40GHz: $\pm 4.08\text{ dB}$

4.6 Appendix F: Photographs of EUT

Please refer to the File of **ISL-22LR0199P**

--- END ---