

# TEST REPORT

of

## RE Directive (2014/53/EU) EN50566: 2017 / EN50663: 2017

**Product :** Bluetooth 5.1 Module

**Brand Name:** Fanstel

**Model:** BM833F , BM833E, BM833

**Model Difference:** Please see page 5 for detail

**Applicant:** Fanstel Corporation, Taipei

**Address:** 10F-10, No. 79, Sec. 1, Hsin Tai Wu Rd.,  
Hsi-Chih, New Taipei City 221 Taiwan

### Test Performed by:

#### International Standards Laboratory Corp.

<LT Lab.>

\*Address:

No. 120, Lane 180, Hsin Ho Rd.,

Lung-Tan Dist., Tao Yuan City 325, Taiwan

\*Tel : 886-3-407-1718; Fax: 886-3-407-1738

Report No.: **ISL-19LR247EMPE**

Issue Date : **2019/10/21**

Test results given in this report apply only to the specific sample(s) tested and are traceable to national or international standard through calibration of the equipment and evaluating measurement uncertainty herein.


This test report shall not be reproduced except in full, without the written approval of International Standards Laboratory Corp.

## VERIFICATION OF COMPLIANCE

**Applicant:** Fanstel Corporation, Taipei  
**Equipment Under Test:** Bluetooth 5.1 Module  
**Brand Name:** Fanstel  
**Model Number:** BM833F , BM833E, BM833  
**Model Different:** Please see page 5 for detail  
**Date of Test:** 2019/08/19 ~ 2019/10/18  
**Date of EUT Received:** 2019/08/19

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
EN50566: 2017 EN50663: 2017	Complied

The above equipment was tested by International Standards Laboratory Corp.. for compliance with the requirements set forth in the European Standard EN 50566: 2017 and EN 50663: 2017 under 3.1 (a) of RE Directive 2014/53/EU. The results of in this report apply to the product system that was used only.

<i>Test By:</i>	 <hr style="border: 0; border-top: 1px solid black;"/> <i>Weitin Chen / Senior Engineer</i>	<i>Date:</i>	2019/10/21
<i>Prepared By:</i>	 <hr style="border: 0; border-top: 1px solid black;"/> <i>Gigi Yeh / Senior Engineer</i>	<i>Date:</i>	2019/10/21
<i>Approved By:</i>	 <hr style="border: 0; border-top: 1px solid black;"/> <i>Jerry Liu / Technical Manager</i>	<i>Date:</i>	2019/10/21

## Version

Version No.	Date	Description
00	2019/10/21	Initial creation of document

## TABLE OF CONTENTS

<b>1.</b>	<b>Description of Equipment under Test (EUT) .....</b>	<b>5</b>
<b>2.</b>	<b>Description of Test Modes .....</b>	<b>7</b>
<b>3.</b>	<b>General Description of Applied Standards.....</b>	<b>7</b>
<b>4.</b>	<b>RF Exposure Evaluations .....</b>	<b>8</b>
	<b>Photographs of EUT .....</b>	<b>11</b>

## 1. Description of Equipment under Test (EUT)

General:

Product Name:	Bluetooth 5.1 Module
Brand Name:	Fanstel
Model Name:	BM833F , BM833E, BM833
Model Difference:	Please see table below for detail.
Type of Equipment:	Stand-alone equipment
Temperature Range:	-40°C to +85°C
Simultaneous transmissions:	Yes
Geo-location capability:	No
Power Supply	5Vdc by USB port

### Model Summaries

module	BM833	BM833F	BM833E
SoC	nRF52833 QIAA	nRF52833 QIAA	nRF52833 QIAA
Flash/RAM	512KB/128KB	512KB/128KB	512KB/128KB
Size	10.2x15x1.9mm	15x20.6x1.9mm	10.2x15x1.9mm
GPIO	42	42	42
Antenna	PCB trace	PCB trace	u.FL
Antenna Gain	-0.56dB	0.51dBi	0dBi

Bluetooth Version	BT 5.1
Frequency Range:	2402 – 2480MHz
Channel number:	40 channels
Modulation type:	Wide band Modulation
Transmit Power: (EIRP)	BM833E : 6.00 dBm BM833F : 6.51 dBm
Dwell Time	N/A
Operating Mode	Point-to-Point
Adaptive/ Non-Adaptive	Non-Adaptive
LBT (Listen Before Talk)	Yes
	<input checked="" type="checkbox"/> Adaptive Frequency Hopping using LBT based DAA <input type="checkbox"/> Adaptive Frequency Hopping using other forms of DAA (non-LBT based) <input type="checkbox"/> Short Control Signaling Transmissions
Occupied Channel Bandwidth	Within 2400-2483.5MHz
Duty Cycle	N/A
Antenna Beam forming	No
Antenna Designation:	PCB Antenna, BM833 : -0.56 dBi PCB Antenna, BM833F : 0.51 dBi Dipole Antenna, BM833E : 0 dBi

The EUT is compliance with BLE Standard.

## 2. Description of Test Modes

The EUT has been tested under Operating condition. And used to control the EUT for staying in continuous transmitting mode is programmed. Channel low, mid, and High for each modulation type are chosen for testing.

## 3. General Description of Applied Standards

The EUT According to the Specifications, it must comply with the requirements of the following standards:

EN 50566:2017 – Product standard to demonstrate the compliance of wireless communication devices with the basic restrictions and exposure limit values related to human exposure to electromagnetic fields in the frequency range from 30 MHz to 6 GHz: hand-held and body mounted devices in close proximity to the human body

EN 50663:2017 – Generic standard for assessment of low power electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (10 MHz - 300 GHz)

EN 62311:2008 – Generic standard to demonstrate the compliance of electrical apparatus with the basic restrictions related to human exposure to electromagnetic fields (0Hz-300GHz)

EN 62479:2010 – Assessment of the compliance of low power electronic and electrical equipment with the basic restrictions related to human exposure to electromagnetic fields (10MHz to 300GHz)

## 4. RF Exposure Evaluations

### 4.1. Standards:

According to section 4.2 Low-power exclusion level ( $P_{max}$ ) of EN 62479: 2010 and Annex A, Table A.1 – Example values of SAR-based  $P_{max}$  for some cases described by ICNIRP, IEEE Std C95.1-1999 and IEEE Std C95.1-2005

**Table A.1 – Example values of SAR-based  $P_{max}$  for some cases described by ICNIRP, IEEE Std C95.1-1999 and IEEE Std C95.1-2005**

Guideline / Standard	SAR limit, $SAR_{max}$ W/kg	Averaging mass, $m$ g	$P_{max}$ mW	Exposure tier <sup>a</sup>	Region of body <sup>a</sup>
ICNIRP [1]	2	10	20	General public	Head and trunk
	4	10	40	General public	Limbs
	10	10	100	Occupational	Head and trunk
	20	10	200	Occupational	Limbs
IEEE Std C95.1-1999 [2]	1,6	1	1,6	Uncontrolled environment	Head, trunk, arms, legs
	4	10	40	Uncontrolled environment	Hands, wrists, feet and ankles
	8	1	8	Controlled environment	Head, trunk, arms, legs
	20	10	200	Controlled environment	Hands, wrists, feet and ankles
IEEE Std C95.1-2005 [3]	2	10	20	Action level	Body except extremities and pinnae
	4	10	40	Action level	Extremities and pinnae
	10	10	100	Controlled environment	Body except extremities and pinnae
	20	10	200	Controlled environment	Extremities and pinnae

<sup>a</sup> Consult the appropriate standard for more information and definitions of terms.

### 4.2. Classification of the assessment method:

The antenna of the product, under normal use condition is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20 cm separation distance and the prohibition of operating to a person has been printed on the user's manual. So, this product under normal use is located on electromagnetic far field between the human body.

#### Far Field Calculation Formula

$$E = \frac{\sqrt{30PG(\theta, \phi)}}{r}$$

$G$  = antenna gain relative to an isotropic antenna  
 $\theta, \phi$  = elevation and azimuth angles to point of investigation  
 $r$  = distance from observation point to the antenna

#### **4.3. EUT operating condition:**

The software provided by Manufacturer enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

**4.4. Test Results:**

**E-Field Strength Calculation: EN 62311: 2008**

**Mode: BLE with Dipole Antenna**

**Ambient temperature: 25°C      Relative humidity: 60%      Test Date: 2019/08/15**

Antenna Gain=                    0.00      dBi  
 Distance to human body=                    20            cm  
 Duty Cycle=                    0.99

Frequency	EIRP (dBm)	EIRP (mW)	E-Field Strength (V/m)	E-Field Strength Limit (V/m)	PASS/ FAIL
2402.00	5.70	3.72	1.66	61.00	PASS
2442.00	6.00	3.98	1.72	61.00	PASS
2480.00	6.00	3.98	1.72	61.00	PASS

**E-Field Strength Calculation: EN 62311: 2008**

**Mode: BLE with PCB Antenna**

**Ambient temperature: 25°C      Relative humidity: 60%      Test Date: 2019/08/15**

Antenna Gain=                    0.51      dBi  
 Distance to human body=                    20            cm  
 Duty Cycle=                    0.99

Frequency	EIRP (dBm)	EIRP (mW)	E-Field Strength (V/m)	E-Field Strength Limit (V/m)	PASS/ FAIL
2402.00	6.21	4.18	1.76	61.00	PASS
2442.00	6.51	4.48	1.82	61.00	PASS
2480.00	6.51	4.48	1.82	61.00	PASS

**Evaluation Results:**

The Calculation of E-Field Strength is less than EN 62311 E-Field Strength limit 61V/m at 2.4GHz.

# **APPENDIX 1**

## **Photographs of EUT**

*Refer to ISL-19LR247E328*

*~ End of Report ~*