

TEST REPORT

of

FCC Part 15 Subpart C AND CANADA RSS-247

☒ New Application; ☐ Class I PC; ☐ Class II PC

Product : LoRa transceiver Module
Brand: Fanstel
Model: LR62E1, LR62C
Model Difference: Antenna difference
FCC ID: X8WLR62E1
IC: 4100A-LR62E1
FCC Rule Part: §15.247, Cat: DTS
IC Rule Part: RSS-247 issue 2: 2017
RSS-Gen issue 5: 2018
Applicant: Fanstel Corporation, Taipei
Address: 10F-10, No. 79, Sec. 1, Hsin Tai Wu Rd.,
Hsi-Chih, New Taipei City 221 Taiwan

Test Performed by:



International Standards Laboratory Corp. LT Lab.

TEL: +886-3-263-8888 FAX: +886-3-263-8899

No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist., Tao Yuan City 325, Taiwan

Report No.: ISL-23LR0182FCIC

Issue Date : December 26, 2023



FCC Registration Number: 487532

Test results given in this report apply only to the specific sample(s) tested and are traceable to national or international standard through calibration of the equipment and evaluating measurement uncertainty herein.

According to customer agreement, the laboratory issues test reports based on the regulations or standards specifications, the measurement uncertainty is not considered in conformity decision rules.

This test report shall not be reproduced except in full, without the written approval of International Standards Laboratory Corp.

VERIFICATION OF COMPLIANCE

Applicant: Fanstel Corporation, Taipei

Product Description: LoRa transceiver Module

Brand Name: Fanstel

Model No.: LR62E1, LR62C

Model Difference: Antenna difference

FCC ID: X8WLR62E1

IC: 4100A-LR62E1

Date of test: 2023/12/13 ~ 2023/12/25

Date of EUT Received: 2023/12/13

We hereby certify that:

All the tests in this report have been performed and recorded in accordance with the standards described above and performed by an independent electromagnetic compatibility consultant, International Standards Laboratory Corp.

The test results contained in this report accurately represent the measurements of the characteristics and the energy generated by sample equipment under test at the time of the test. The sample equipment tested as described in this report is in compliance with the limits of above standards.

Test By:

Weitin Chen

Date:

2023/12/26

Weitin Chen / Senior Engineer

Prepared By:

Gigi yeh

Date:

2023/12/26

Gigi Yeh / Senior Engineer

Approved By:

Jerry Liu

Date:

2023/12/26

Jerry Liu / Manager

Version

Version No.	Date	Description
00	2023/12/26	Initial creation of document

Uncertainty of Measurement

Parameter	Uncertainty (k=2)
Conducted Emission (AC power line)	± 0.64 dB
Spurious emissions, radiated	± 3.5 dB
RF power, conducted	± 1.6 dB
Power Density	± 1.7 dB
RF Frequency	± 0.0041 %
Time	± 0.01 %
DC Voltage	± 0.03 %

Table of Contents

1	General Information	6
1.1	Related Submittal(s) / Grant (s)	8
1.2	Test Methodology	8
1.3	Test Facility	8
1.4	Special Accessories	8
1.5	Equipment Modifications	8
1.6	Reference	8
2	System Test Configuration	9
2.1	EUT Configuration	9
2.2	EUT Exercise	9
2.3	Test Procedure	9
2.4	Configuration of Tested System	10
2.5	Duty Cycle	11
3	Summary of Test Results	12
4	Description of Test Modes	12
5	Conducted Emission Test	13
5.1	Standard Applicable:	13
5.2	Measurement Equipment Used:	13
5.3	EUT Setup:	13
5.4	Measurement Procedure:	14
5.5	Measurement Result:	14
6	Peak Output Power Measurement	17
6.1	Standard Applicable:	17
6.2	Measurement Equipment Used:	18
6.3	Test Set-up:	19
6.4	Measurement Procedure:	19
6.5	Measurement Result:	19
7	6dB Bandwidth & 99% Bandwidth	20
7.1	Standard Applicable:	20
7.2	Measurement Equipment Used:	20
7.3	Test Set-up:	20
7.4	Measurement Procedure:	20
7.5	Measurement Result:	20
8	Spurious Emission Test	24
8.1	Standard Applicable	24
8.2	Measurement Equipment Used:	24
8.3	Test SET-UP:	24
8.4	Measurement Procedure:	25
8.5	Field Strength Calculation	26
8.6	Measurement Result:	26
9	100kHz Bandwidth of Band Edges Measurement	45
9.1	Standard Applicable:	45
9.2	Measurement Equipment Used:	46
9.3	Test SET-UP:	47
9.4	Measurement Procedure:	48
9.5	Field Strength Calculation:	48
9.6	Measurement Result:	48
10	Peak Power Spectral Density	49
10.1	Standard Applicable:	49

10.2	Measurement Equipment Used:	49
10.3	Test Set-up:	49
10.4	Measurement Procedure:	49
10.5	Measurement Result:	49
11	Antenna Requirement	52
11.1	Standard Applicable:	52
11.2	Antenna Connected Construction:	53
Appendix 1		54
Photographs of Set Up		54
Appendix 2		69
Photographs of EUT		69

1 General Information

General Information	
Product Name:	LoRa transceiver Module
Brand Name:	Fanstel
Model Name:	LR62E1
Series Model No.	LR62C
Model Difference:	Antenna Difference:
Power Supply:	5VdC from USB
LoRa Information	
LoRa Modular:	SX1262
Frequency Range:	902 – 928MHz
Max Output Power:	20.13 dBm
Channel number:	25 channels
Modulation type:	CCS
PMN (Product Marketing Name)	LR62E1
HVIN (Hardware Version Identification Number)	LR62E1, LR62C
FVIN (Firmware Version Identification Number)	SemtechLoraTestV1.0
Test SoftWare Version	SX1262 915.5MHz Demo Kit ver.180110
RF power setting:	Tx Pow: 20dBm

	Antenna Type	Brand	Model	Peak Gain	Frequency Range	Connector Type
1	Dipole	Fanstel	YZ868-915-RPSMA-200	1.46dBi	868-930 MHz	RPSMA
2	Flexible PCB	TE Connectivity	2195835-5	4.50dBi	868-930 MHz	U.FL
3	CHIP	onewave	WAN031003F0391SM03	1.32dBi	898-928 MHz	-----

Remark: The above DUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Channel Number List:

25 channels are provided DTS Mode (500kHz Bandwidth):

Operation Frequency each of channel					
Channel	Frequency	Channel	Frequency	Channel	Frequency
0	902.5	10	912.5	20	922.5
1	903.5	11	913.5	21	923.5
2	904.5	12	914.5	22	924.5
3	905.5	13	915.5	23	925.5
4	906.5	14	916.5	24	926.5
5	907.5	15	917.5	25	927.5
6	908.5	16	918.5		
7	909.5	17	919.5		
8	910.5	18	920.5		
9	911.5	19	921.5		

Test Mode:

Test mode	量測項目 產品型號_天線 Type	6dB Bandwidth	Power Density	Output Power	Radiation
Config 1	LR62E1 Dipole Ant.	√	√	√	√
Config 2	LR62E1 PCB Ant.				√
Config 3	LR62C Chip Ant.				√

1.1 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID: X8WLR62E1** filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules and **IC: 4100A-LR62E1** filing to comply with Industry Canada RSS-247 issue 2: 2017.

1.2 Test Methodology

Both conducted and radiated testing were performed according to the procedures in ANSI C63.10: 2013. Radiated testing was performed at an antenna to EUT distance 3 meters.

1.3 Test Facility

The measurement facilities used to collect the 3m Radiated Emission and AC power line conducted data are located on the address of **International Standards Laboratory Corp.** <LT Lab.> No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist., Tao Yuan City 325, Taiwan which are constructed and calibrated to meet the FCC requirements in documents ANSI C63.10: 2013. FCC Registration Number is: 487532; Designation Number is: TW0997, Canada Registration Number: 4067B-4.

1.4 Special Accessories

Not available for this EUT intended for grant.

1.5 Equipment Modifications

Not available for this EUT intended for grant.

1.6 Reference

KDB Document: 558074 D01 15.247 Meas Guidance v05r02.

2 System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The EUT (Transmitter) was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements.

2.3 Test Procedure

2.3.1 Conducted Emissions

The EUT is placed on a turn table which is 0.8 m above ground plane. According to the requirements in Section 6 and RSS-Gen Issue 5, Amendment 1: 2019. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR 16-1-1 Quasi-Peak and Average detector mode.

2.3.2 Radiated Emissions

The EUT is placed on a turn table which is 0.8/1.5 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes and measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made “while keeping the antenna in the ‘cone of radiation’ from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response.” Is still within the 3dB illumination BW of the measurement antenna. According to the requirements in Section 8 and 13 and Subclause 8.3.1.2 of ANSI C63.10: 2013.

2.4 Configuration of Tested System

Fig. 2-1 Configuration



Table 2-1 Equipment Used in Tested System

Item	Equipment	Mfr/Brand	Model/ Type No.	Series No.	Data Cable	Power Cord
1	Adapter	Apple	A1385	N/A	N/A	100cm

Note: All the above equipment/cables were placed in worse case positions to maximize emission signals during emission test.

Grounding: Grounding was in accordance with the manufacturer's requirements and conditions for the intended use.

2.5 Duty Cycle


If duty cycle of test signal is $\geq 98\%$, duty factor is not required.

If duty cycle of test signal is $< 98\%$, duty factor shall be considered.

The output power = measured power + duty factor.

Mode	ON time (ms)	Total time (ms)	Duty Cycle	Duty Factor	1/Ton (kHz)	VBW for average detector (kHz)
LoRa	4.200	10.150	0.414	3.832	0.238	0.300

LoRa



3 Summary of Test Results

FCC Rules	Description Of Test	Result
§15.207(a) RSS-Gen §8.8	AC Power Line Conducted Emission	Compliant
§15.247(b) (3),(4) RSS-247 issue 2, §5.4(4)	Peak Output Power/ EIRP	Compliant
§15.247(a)(2) RSS-247 issue 2, §5.2(1) RSS-Gen §6.6	6dB & 99% Power Bandwidth	Compliant
§15.247(d) RSS-247 issue 2, §5.5	100 kHz Bandwidth Of Frequency Band Edges	Compliant
§15.247(d) RSS-247 issue 2, §5.5	Spurious Emission	Compliant
§15.247(e) RSS-247 issue 2, §5.2(2)	Peak Power Density	Compliant
§15.203 RSS-GEN 8.3	Antenna Requirement	Compliant

4 Description of Test Modes

The EUT has been tested under engineering operating condition.

Test program used to control the EUT for staying in continuous transmitting mode is programmed.

Channel low (902.5MHz) 、mid (915.5MHz) and high (927.5MHz) with highest data rate are chosen for full testing.

5 Conducted Emission Test

5.1 Standard Applicable:

According to §15.207 and RSS-Gen §7.2.4, frequency range within 150kHz to 30MHz shall not exceed the Limit table as below.

Frequency range MHz	Limits dB(uV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50
Note 1.The lower limit shall apply at the transition frequencies 2.The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.		

5.2 Measurement Equipment Used:

Location	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Conduction 03	EMI Receiver 20	R&S	ESR7	101326	05/25/2023	05/25/2024
Conduction 03	Chamber05-1 Cable	WOKEN	CFD 300-NL	Chamber05-1 Cable	08/25/2023	08/25/2024
Conduction 03	LISN 19	R&S	ENV216	101425	11/23/2023	11/23/2024
Conduction 03	LISN 22	ROHDE & SCHWARZ	ENV216	101478	11/01/2023	11/01/2024
Conduction 03	LISN 24	SCHWARZ-BECK	NNLK 8121	8121-829	07/27/2023	07/27/2024
Conduction 03	ISN T8 CAT6A_03	SCHWARZ-BECK	NTFM 8158	NTFM 8158-00367	06/30/2023	06/30/2024
Conduction 03	ISN T4 06	Teseq GmbH	ISN T400A	28574	10/12/2023	10/12/2024
Conduction 03	ISN T8 09	Teseq GmbH	ISN T800	36190	09/26/2023	09/26/2024
Conduction 03	CDN ISN ST08A_1	Teseq GmbH	CDN ISN ST08A	43352	09/27/2023	09/27/2024
Conduction 03	Capacitive Voltage Probe 01	SCHAFFNER	CVP 2200A	18711	02/22/2023	02/22/2024
Conduction 03	Current Probe	SCHAFFNER	SMZ 11	18030	02/22/2023	02/22/2024

5.3 EUT Setup:

1. The conducted emission tests were performed in the test site, using the setup in accordance with the ANSI C63.10-2013.
2. The AC/DC Power adaptor of PC was plug-in LISN. The EUT was placed flushed with the rear of the table.
3. The LISN was connected with 120Vac/60Hz power source.

5.4 Measurement Procedure:

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.
4. Both 120V & 240V have been verified, and 120V/60Hz was defined as the worst-case and record in the report.

5.5 Measurement Result:

Note: Refer to next page for measurement data and plots.

AC POWER LINE CONDUCTED EMISSION TEST DATA



Address: No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
Tao Yuan City 325, Taiwan.
Tel: 03-2638888


Conducted Emission Measurement

Date: 2023/12/15

operator: Tom Ouyang

Temperature: 26 °C

Humidity: 59 %



Site: Conduction 03

Phase: L1

No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1*	0.557	34.33	26.85	9.70	44.03	56.00	-11.97	36.55	46.00	-9.45
2	0.802	29.65	21.60	9.71	39.36	56.00	-16.64	31.31	46.00	-14.69
3	1.556	27.88	18.38	9.75	37.63	56.00	-18.37	28.13	46.00	-17.87
4	2.159	27.58	16.40	9.77	37.35	56.00	-18.65	26.17	46.00	-19.83
5	2.861	27.62	16.71	9.79	37.41	56.00	-18.59	26.50	46.00	-19.50
6	9.582	27.88	17.86	9.92	37.80	60.00	-22.20	27.78	50.00	-22.22



Address: No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
Tao Yuan City 325, Taiwan.
Tel: 03-2638888


Conducted Emission Measurement

Date: 2023/12/15

operator: Tom Ouyang

Temperature: 26 °C

Humidity: 59 %



Site: Conduction 03

Phase: N

No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1*	0.555	31.53	25.39	9.70	41.23	56.00	-14.77	35.09	46.00	-10.91
2	0.832	24.17	18.31	9.73	33.90	56.00	-22.10	28.04	46.00	-17.96
3	1.556	22.68	15.15	9.76	32.44	56.00	-23.56	24.91	46.00	-21.09
4	2.263	22.34	13.99	9.78	32.12	56.00	-23.88	23.77	46.00	-22.23
5	3.053	22.12	13.58	9.80	31.92	56.00	-24.08	23.38	46.00	-22.62
6	9.787	23.34	14.48	9.96	33.30	60.00	-26.70	24.44	50.00	-25.56

6 Peak Output Power Measurement

6.1 Standard Applicable:

According to §15.247(b)(3),(4)(b)

(3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(c) Operation with directional antenna gains greater than 6 dBi.

(1) Fixed point-to-point operation:

(i) Systems operating in the 2400-2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

(ii) Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted output power.

According to RSS-247 issue 2, §5.4


(4) For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W. Except as provided in Section 5.4(5), the e.i.r.p. shall not exceed 4 W.

As an alternative to a peak power measurement, compliance can be based on a measurement of the maximum conducted output power. The maximum conducted output power is the total transmit power delivered to all antennas and antenna elements, averaged across all symbols in the signalling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or transmitting at a reduced power level. If multiple modes of operation are implemented, the maximum conducted output power is the highest total transmit power occurring in any mode.

6.2 Measurement Equipment Used:

Location Conducted	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Conducted	Power Meter	Anritsu	ML2495A	1116010	09/27/2023	09/27/2024
Conducted	Power Sensor	Anritsu	MA2411B	34NKF50	09/27/2023	09/27/2024
Conducted	Temperature Chamber	KSON	THS-B4H100	2287	05/17/2023	05/17/2024
Conducted	DC Power supply	ABM	8185D	N/A	01/04/2023	01/04/2024
Conducted	AC Power supply	EXTECH	CFC105W	NA	N/A	N/A
Conducted	Spectrum analyzer	Keysight	N9010A	MY56070257	09/26/2023	09/26/2024
Conducted	Test Software	DARE	Radiation Ver:2013.1.23	NA	NA	NA
Conducted	Wideband Radio Comm. Tester	R&S	CMW500	1201.002K50108793-JG	10/26/2023	10/26/2024
Conducted	Radio Communication Test Station	Anritsu	MT8000A	6272539604	08/30/2023	08/30/2024
Conducted	MT8000A Test Software	Anritsu	MX800000A Application Launcher v10.10.5.0	NA	NA	NA
Conducted	BT Simulator	Agilent	N4010A	MY48100200	NA	NA
Conducted	Signal Generator	Keysight	N5182B	MY53052399	12/28/2022	12/28/2023
Conducted (TS8997)	Wideband Radio Comm. Tester	R&S	CMW500	168811	09/13/2023	09/13/2024
Conducted (TS8997)	UP/DOWN converter	R&S	CMW-Z800A	100566	09/13/2023	09/13/2024
Conducted (TS8997)	Signal Generator	R&S	SMB100A	183701	09/14/2023	09/14/2024
Conducted (TS8997)	Vector Signal Generator	R&S	SMM100A	101908	09/13/2023	09/13/2024
Conducted (TS8997)	Signal analyzer 40GHz	R&S	FSV40	101884	09/13/2023	09/13/2024
Conducted (TS8997)	OSP150 extension unit CAM-BUS	R&S	OSP150	101107	09/15/2023	09/15/2024
Conducted (TS8997)	Test Software	R&S	EMC32 Ver:11.60.00	NA	NA	NA

6.3 Test Set-up:



6.4 Measurement Procedure:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power meter
3. Record the max. reading.
4. Repeat above procedures until all frequency measured were complete.

6.5 Measurement Result:

LORA

Frequency (MHz)	Peak Reading Power (dBm)	Duty Factor (dB)	Output Power (dBm)	Output Power (W)	Limit (W)
Low	20.13	-----	20.13	30.00	1
Mid	19.96	-----	19.96	30.00	1
High	19.76	-----	19.76	30.00	1

7 6dB Bandwidth & 99% Bandwidth

7.1 Standard Applicable:

According to §15.247(a)(2), Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500kHz.

According to RSS-247 issue 2, §5.2

(1) The minimum 6 dB bandwidth shall be 500 kHz.

7.2 Measurement Equipment Used:

Refer to section 6.2 for details.

7.3 Test Set-up:

Refer to section 6.3 for details.

7.4 Measurement Procedure:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW=100kHz, VBW = 3*RBW, Span= cover the complete power envelope of the signal of the UUT Sweep=auto
4. Mark the peak frequency and -6dB (upper and lower) frequency.
5. Repeat above procedures until all frequency measured were complete.

7.5 Measurement Result:


LoRa

Frequency (MHz)	6dB Bandwidth (MHz)	99% OBW (MHz)	Limit (kHz)	Result
Low	0.574	0.518	> 500	PASS
Mid	0.578	0.518	> 500	PASS
High	0.573	0.539	> 500	PASS


Note: Refer to next page for plots.

RoLa


6dB Bandwidth Test Data CH-Low



6dB Band Width Test Data CH-Mid




6dB Band Width Test Data CH-High




RoLa


99% Bandwidth Test Data CH-Low



99% Band Width Test Data CH-Mid



99% Band Width Test Data CH-High



8 Spurious Emission Test

8.1 Standard Applicable

According to §15.247(c), all other emissions outside these bands shall not exceed the general radiated emission limits specified in §15.209(a). And according to §15.33(a)(1), for an intentional radiator operates below 10GHz, the frequency range of measurements: to the tenth harmonic of the highest fundamental frequency or to 40GHz, whichever is lower.

According to RSS-247 issue 2, §5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

8.2 Measurement Equipment Used:

8.2.1 Conducted Emission at antenna port:

Refer to section 6.2 for details.

8.2.2 Radiated emission:

Refer to section 7.2 for details.

8.3 Test SET-UP:

8.3.1 Conducted Emission at antenna port:

Refer to section 6.3 for details.

8.3.2 Radiated emission:

Refer to section 7.3 for details.

8.4 Measurement Procedure:

1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. The turn table shall rotate 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emissions.
4. When measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made “while keeping the antenna in the ‘cone of radiation’ from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response.” is still within the 3dB illumination BW of the measurement antenna.
5. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
6. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
7. Repeat above procedures until all frequency measured were complete.

Test receiver setting	: Blew 1GHz
Detector	: Average(9kHz – 90kHz, 110kHz – 90kHz), Quasi-Peak
Bandwidth	: 200Hz, 120kHz
Test spectrum setting	: Above 1GHz
Peak	: RBW=1MHz, VBW=3MHz
Average	: RBW=1MHz, VBW \geq 1/Ton

8.5 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where	FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
	RA = Reading Amplitude	AG = Amplifier Gain
	AF = Antenna Factor	

8.6 Measurement Result:

Note: Refer to next page spectrum analyzer data chart and tabular data sheets.

Radiated Spurious Emission Measurement Result (below 1GHz) Config 1

Operation Mode	TX CH Low	Test Date	2023/12/22
Fundamental Frequency	902.5MHz	Test By	Weitin
Temperature	23 °C	Pol	Ver./Hor
Humidity	69 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	170.65	31.17	-10.27	20.90	43.50	-22.60	Peak	VERTICAL
2	299.66	30.72	-9.38	21.34	46.00	-24.66	Peak	VERTICAL
3	385.02	29.27	-6.95	22.32	46.00	-23.68	Peak	VERTICAL
4	487.84	27.26	-4.36	22.90	46.00	-23.10	Peak	VERTICAL
5	612.97	27.26	-1.40	25.86	46.00	-20.14	Peak	VERTICAL
6	772.05	31.24	1.32	32.56	46.00	-13.44	Peak	VERTICAL
1	167.74	31.50	-10.17	21.33	43.50	-22.17	Peak	HORIZONTAL
2	280.26	30.78	-9.84	20.94	46.00	-25.06	Peak	HORIZONTAL
3	378.23	29.39	-7.14	22.25	46.00	-23.75	Peak	HORIZONTAL
4	491.72	26.88	-4.32	22.56	46.00	-23.44	Peak	HORIZONTAL
5	626.55	28.89	-1.32	27.57	46.00	-18.43	Peak	HORIZONTAL
6	714.82	30.01	0.06	30.07	46.00	-15.93	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (below 1GHz) Config 1

Operation Mode	TX CH Mid	Test Date	2023/12/22
Fundamental Frequency	915.5MHz	Test By	Weitin
Temperature	23 °C	Pol	Ver./Hor
Humidity	69 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	151.25	30.87	-10.01	20.86	43.50	-22.64	Peak	VERTICAL
2	285.11	31.05	-9.62	21.43	46.00	-24.57	Peak	VERTICAL
3	448.07	27.20	-5.04	22.16	46.00	-23.84	Peak	VERTICAL
4	557.68	27.89	-3.05	24.84	46.00	-21.16	Peak	VERTICAL
5	697.36	29.85	-0.14	29.71	46.00	-16.29	Peak	VERTICAL
6	772.05	30.35	1.32	31.67	46.00	-14.33	Peak	VERTICAL
1	158.04	30.84	-9.98	20.86	43.50	-22.64	Peak	HORIZONTAL
2	288.02	30.48	-9.55	20.93	46.00	-25.07	Peak	HORIZONTAL
3	370.47	29.10	-7.48	21.62	46.00	-24.38	Peak	HORIZONTAL
4	533.43	26.25	-3.49	22.76	46.00	-23.24	Peak	HORIZONTAL
5	598.42	27.79	-1.74	26.05	46.00	-19.95	Peak	HORIZONTAL
6	692.51	29.00	-0.26	28.74	46.00	-17.26	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (below 1GHz) Config 1

Operation Mode TX CH High
Fundamental Frequency 927.5MHz
Temperature 23 °C
Humidity 69 %

Test Date 2023/12/22
Test By Weitin
Pol Ver./Hor

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	158.04	31.23	-9.98	21.25	43.50	-22.25	Peak	VERTICAL
2	287.05	30.63	-9.58	21.05	46.00	-24.95	Peak	VERTICAL
3	447.10	27.60	-5.08	22.52	46.00	-23.48	Peak	VERTICAL
4	555.74	27.03	-3.09	23.94	46.00	-22.06	Peak	VERTICAL
5	613.94	27.42	-1.40	26.02	46.00	-19.98	Peak	VERTICAL
6	903.00	29.69	2.67	32.36	46.00	-13.64	Peak	VERTICAL
1	168.71	30.75	-10.13	20.62	43.50	-22.88	Peak	HORIZONTAL
2	277.35	30.91	-9.90	21.01	46.00	-24.99	Peak	HORIZONTAL
3	378.23	28.67	-7.14	21.53	46.00	-24.47	Peak	HORIZONTAL
4	480.08	27.17	-4.49	22.68	46.00	-23.32	Peak	HORIZONTAL
5	573.20	27.01	-2.65	24.36	46.00	-21.64	Peak	HORIZONTAL
6	776.90	29.92	1.24	31.16	46.00	-14.84	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (below 1GHz) Config 2

Operation Mode	TX CH Low	Test Date	2023/12/22
Fundamental Frequency	902.5MHz	Test By	Weitin
Temperature	23 °C	Pol	Ver./Hor
Humidity	69 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	149.31	31.10	-10.09	21.01	43.50	-22.49	Peak	VERTICAL
2	269.59	30.53	-10.21	20.32	46.00	-25.68	Peak	VERTICAL
3	434.49	27.63	-5.38	22.25	46.00	-23.75	Peak	VERTICAL
4	573.20	27.61	-2.65	24.96	46.00	-21.04	Peak	VERTICAL
5	701.24	29.19	-0.09	29.10	46.00	-16.90	Peak	VERTICAL
6	799.21	29.61	1.43	31.04	46.00	-14.96	Peak	VERTICAL
1	166.77	31.37	-10.19	21.18	43.50	-22.32	Peak	HORIZONTAL
2	258.92	31.43	-10.77	20.66	46.00	-25.34	Peak	HORIZONTAL
3	363.68	30.25	-7.97	22.28	46.00	-23.72	Peak	HORIZONTAL
4	442.25	28.12	-5.19	22.93	46.00	-23.07	Peak	HORIZONTAL
5	642.07	28.29	-0.95	27.34	46.00	-18.66	Peak	HORIZONTAL
6	771.08	30.02	1.33	31.35	46.00	-14.65	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (below 1GHz) Config 2

Operation Mode	TX CH Mid	Test Date	2023/12/22
Fundamental Frequency	915.5MHz	Test By	Weitin
Temperature	23 °C	Pol	Ver./Hor
Humidity	69 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	167.74	30.78	-10.17	20.61	43.50	-22.89	Peak	VERTICAL
2	275.41	31.20	-9.95	21.25	46.00	-24.75	Peak	VERTICAL
3	377.26	29.25	-7.18	22.07	46.00	-23.93	Peak	VERTICAL
4	515.97	27.03	-3.83	23.20	46.00	-22.80	Peak	VERTICAL
5	636.25	28.02	-1.08	26.94	46.00	-19.06	Peak	VERTICAL
6	770.11	29.61	1.35	30.96	46.00	-15.04	Peak	VERTICAL
1	146.40	31.33	-10.06	21.27	43.50	-22.23	Peak	HORIZONTAL
2	275.41	30.54	-9.95	20.59	46.00	-25.41	Peak	HORIZONTAL
3	374.35	29.01	-7.31	21.70	46.00	-24.30	Peak	HORIZONTAL
4	565.44	26.78	-2.76	24.02	46.00	-21.98	Peak	HORIZONTAL
5	661.47	29.10	-0.82	28.28	46.00	-17.72	Peak	HORIZONTAL
6	767.20	30.17	1.35	31.52	46.00	-14.48	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (below 1GHz) Config 2

Operation Mode TX CH High
Fundamental Frequency 927.5MHz
Temperature 23 °C
Humidity 69 %

Test Date 2023/12/22
Test By Weitin
Pol Ver./Hor

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	148.34	30.60	-10.12	20.48	43.50	-23.02	Peak	VERTICAL
2	271.53	30.69	-10.12	20.57	46.00	-25.43	Peak	VERTICAL
3	366.59	29.80	-7.78	22.02	46.00	-23.98	Peak	VERTICAL
4	492.69	26.75	-4.30	22.45	46.00	-23.55	Peak	VERTICAL
5	610.06	27.62	-1.41	26.21	46.00	-19.79	Peak	VERTICAL
6	903.00	30.27	2.67	32.94	46.00	-13.06	Peak	VERTICAL
1	161.92	31.00	-10.16	20.84	43.50	-22.66	Peak	HORIZONTAL
2	285.11	31.64	-9.62	22.02	46.00	-23.98	Peak	HORIZONTAL
3	366.59	29.52	-7.78	21.74	46.00	-24.26	Peak	HORIZONTAL
4	433.52	27.64	-5.42	22.22	46.00	-23.78	Peak	HORIZONTAL
5	592.60	27.18	-2.02	25.16	46.00	-20.84	Peak	HORIZONTAL
6	672.14	28.50	-0.68	27.82	46.00	-18.18	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (below 1GHz) Config 3

Operation Mode TX CH Low
Fundamental Frequency 902.5MHz
Temperature 23 °C
Humidity 69 %

Test Date 2023/12/22
Test By Weitin
Pol Ver./Hor

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	164.83	31.08	-10.13	20.95	43.50	-22.55	Peak	VERTICAL
2	268.62	32.90	-10.25	22.65	46.00	-23.35	Peak	VERTICAL
3	332.64	30.70	-8.33	22.37	46.00	-23.63	Peak	VERTICAL
4	383.08	29.37	-7.00	22.37	46.00	-23.63	Peak	VERTICAL
5	518.88	27.52	-3.77	23.75	46.00	-22.25	Peak	VERTICAL
6	798.24	29.91	1.41	31.32	46.00	-14.68	Peak	VERTICAL
1	164.83	30.63	-10.13	20.50	43.50	-23.00	Peak	HORIZONTAL
2	268.62	31.43	-10.25	21.18	46.00	-24.82	Peak	HORIZONTAL
3	329.73	30.11	-8.36	21.75	46.00	-24.25	Peak	HORIZONTAL
4	454.86	27.40	-4.89	22.51	46.00	-23.49	Peak	HORIZONTAL
5	573.20	27.18	-2.65	24.53	46.00	-21.47	Peak	HORIZONTAL
6	682.81	29.47	-0.49	28.98	46.00	-17.02	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (below 1GHz) Config 3

Operation Mode	TX CH Mid	Test Date	2023/12/22
Fundamental Frequency	915.5MHz	Test By	Weitin
Temperature	23 °C	Pol	Ver./Hor
Humidity	69 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	165.80	30.70	-10.06	20.64	43.50	-22.86	Peak	VERTICAL
2	289.96	31.00	-9.51	21.49	46.00	-24.51	Peak	VERTICAL
3	433.52	27.20	-5.42	21.78	46.00	-24.22	Peak	VERTICAL
4	522.76	28.14	-3.73	24.41	46.00	-21.59	Peak	VERTICAL
5	651.77	28.87	-0.85	28.02	46.00	-17.98	Peak	VERTICAL
6	823.46	29.55	1.73	31.28	46.00	-14.72	Peak	VERTICAL
1	165.80	31.57	-10.06	21.51	43.50	-21.99	Peak	HORIZONTAL
2	314.21	30.04	-8.86	21.18	46.00	-24.82	Peak	HORIZONTAL
3	425.76	28.19	-5.76	22.43	46.00	-23.57	Peak	HORIZONTAL
4	581.93	27.58	-2.38	25.20	46.00	-20.80	Peak	HORIZONTAL
5	659.53	28.29	-0.83	27.46	46.00	-18.54	Peak	HORIZONTAL
6	865.17	29.15	1.98	31.13	46.00	-14.87	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (below 1GHz) Config 3

Operation Mode	TX CH High	Test Date	2023/12/22
Fundamental Frequency	927.5MHz	Test By	Weitin
Temperature	23 °C	Pol	Ver./Hor
Humidity	69 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	164.83	31.38	-10.13	21.25	43.50	-22.25	Peak	VERTICAL
2	287.05	30.84	-9.58	21.26	46.00	-24.74	Peak	VERTICAL
3	392.78	28.39	-6.77	21.62	46.00	-24.38	Peak	VERTICAL
4	468.44	27.04	-4.73	22.31	46.00	-23.69	Peak	VERTICAL
5	520.82	27.49	-3.74	23.75	46.00	-22.25	Peak	VERTICAL
6	695.42	28.82	-0.20	28.62	46.00	-17.38	Peak	VERTICAL
1	166.77	31.12	-10.19	20.93	43.50	-22.57	Peak	HORIZONTAL
2	272.50	31.08	-10.08	21.00	46.00	-25.00	Peak	HORIZONTAL
3	337.49	30.31	-8.32	21.99	46.00	-24.01	Peak	HORIZONTAL
4	492.69	27.47	-4.30	23.17	46.00	-22.83	Peak	HORIZONTAL
5	602.30	27.36	-1.60	25.76	46.00	-20.24	Peak	HORIZONTAL
6	770.11	29.88	1.35	31.23	46.00	-14.77	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (above 1GHz) Config 1

Operation Mode	TX CH Low	Test Date	2023/12/22
Fundamental Frequency	902.5MHz	Test By	Weitin
Temperature	23 °C	Pol	Ver./Hor
Humidity	69 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	1805.00	53.27	-0.76	52.51	74.00	-21.49	Peak	VERTICAL
2	2707.50	42.33	2.51	44.84	54.00	-9.16	Average	VERTICAL
3	2707.50	54.71	2.51	57.22	74.00	-16.78	Peak	VERTICAL
1	1805.00	50.34	-0.76	49.58	74.00	-24.42	Peak	HORIZONTAL
2	2707.50	50.59	2.51	53.10	74.00	-20.90	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (above 1GHz) Config 1

Operation Mode	TX CH Mid	Test Date	2023/12/22
Fundamental Frequency	915.5MHz	Test By	Weitin
Temperature	23 °C	Pol	Ver./Hor
Humidity	69 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	1825.00	52.64	-0.47	52.17	74.00	-21.83	Peak	VERTICAL
2	2746.50	42.57	2.47	45.04	54.00	-8.96	Average	VERTICAL
3	2746.50	55.05	2.47	57.52	74.00	-16.48	Peak	VERTICAL
1	1825.00	48.06	-0.47	47.59	74.00	-26.41	Peak	HORIZONTAL
2	2746.50	51.10	2.47	53.57	74.00	-20.43	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (above 1GHz) Config 1

Operation Mode	TX CH High	Test Date	2023/12/22
Fundamental Frequency	927.5MHz	Test By	Weitin
Temperature	23 °C	Pol	Ver./Hor
Humidity	69 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	1855.00	50.74	-0.12	50.62	74.00	-23.38	Peak	VERTICAL
2	2782.50	40.15	2.44	42.59	54.00	-11.41	Average	VERTICAL
3	2782.50	52.91	2.44	55.35	74.00	-18.65	Peak	VERTICAL
1	1721.00	50.78	-2.01	48.77	74.00	-25.23	Peak	HORIZONTAL
2	2782.50	50.25	2.44	52.69	74.00	-21.31	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (above 1GHz) Config 2

Operation Mode TX CH Low
Fundamental Frequency 902.5MHz
Temperature 23 °C
Humidity 69 %

Test Date 2023/12/22
Test By Weitin
Pol Ver./Hor

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2707.50	50.81	2.51	53.32	74.00	-20.68	Peak	VERTICAL
2	5802.00	34.17	8.10	42.27	54.00	-11.73	Average	VERTICAL
3	5802.00	46.10	8.10	54.20	74.00	-19.80	Peak	VERTICAL
1	2707.50	43.77	2.51	46.28	54.00	-7.72	Average	HORIZONTAL
2	2708.00	56.21	2.51	58.72	74.00	-15.28	Peak	HORIZONTAL
3	5816.00	43.52	8.08	51.60	74.00	-22.40	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (above 1GHz) Config 2

Operation Mode	TX CH Mid	Test Date	2023/12/22
Fundamental Frequency	915.5MHz	Test By	Weitin
Temperature	23 °C	Pol	Ver./Hor
Humidity	69 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2746.50	50.56	2.47	53.03	74.00	-20.97	Peak	VERTICAL
2	5809.00	43.06	8.08	51.14	74.00	-22.86	Peak	VERTICAL
1	1826.00	47.87	-0.46	47.41	74.00	-26.59	Peak	HORIZONTAL
2	2746.50	42.77	2.47	45.24	54.00	-8.76	Average	HORIZONTAL
3	2746.50	54.25	2.47	56.72	74.00	-17.28	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (above 1GHz) Config 2

Operation Mode	TX CH High	Test Date	2023/12/22
Fundamental Frequency	927.5MHz	Test By	Weitin
Temperature	23 °C	Pol	Ver./Hor
Humidity	69 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2449.00	45.64	1.43	47.07	74.00	-26.93	Peak	VERTICAL
2	2782.50	49.26	2.44	51.70	74.00	-22.30	Peak	VERTICAL
1	1855.00	45.88	-0.12	45.76	74.00	-28.24	Peak	HORIZONTAL
2	2782.50	34.72	2.44	37.16	54.00	-16.84	Average	HORIZONTAL
3	2782.50	52.46	2.44	54.90	74.00	-19.10	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (above 1GHz) Config 3

Operation Mode	TX CH Low	Test Date	2023/12/22
Fundamental Frequency	902.5MHz	Test By	Weitin
Temperature	23 °C	Pol	Ver./Hor
Humidity	69 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2707.50	49.56	2.51	52.07	74.00	-21.93	Peak	VERTICAL
2	5011.00	33.67	6.53	40.20	74.00	-33.80	Peak	VERTICAL
1	2707.50	50.68	2.51	53.19	74.00	-20.81	Peak	HORIZONTAL
2	6166.00	34.08	8.77	42.85	74.00	-31.15	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (above 1GHz) Config 2

Operation Mode	TX CH Mid	Test Date	2023/12/22
Fundamental Frequency	915.5MHz	Test By	Weitin
Temperature	23 °C	Pol	Ver./Hor
Humidity	69 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2746.50	50.02	2.47	52.49	74.00	-21.51	Peak	VERTICAL
2	5991.00	33.93	8.40	42.33	74.00	-31.67	Peak	VERTICAL
1	2746.50	50.10	2.47	52.57	74.00	-21.43	Peak	HORIZONTAL
2	5683.00	33.09	8.12	41.21	74.00	-32.79	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (above 1GHz) Config 3

Operation Mode	TX CH High	Test Date	2023/12/22
Fundamental Frequency	927.5MHz	Test By	Weitin
Temperature	23 °C	Pol	Ver./Hor
Humidity	69 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2782.50	50.41	2.44	52.85	74.00	-21.15	Peak	VERTICAL
2	5676.00	33.57	8.07	41.64	74.00	-32.36	Peak	VERTICAL
1	2782.50	50.22	2.44	52.66	74.00	-21.34	Peak	HORIZONTAL
2	5151.00	33.71	6.77	40.48	74.00	-33.52	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

9 100kHz Bandwidth of Band Edges Measurement

9.1 Standard Applicable:

According to §15.247(c), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

According to RSS-247 issue 2, §5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(4), the attenuation required shall be 30 dB instead of 20 dB attenuation below the general field strength limits specified in RSS-Gen is not required.

9.2 Measurement Equipment Used:

9.2.1 Conducted Emission at antenna port:

Refer to section 6.2 for details.

9.2.2 Radiated emission:

Location Conducted	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Chamber 19	Signal analyzer	R&S	FSV40	101919	08/16/2023	08/16/2024
Chamber 19	EMI Receiver	R&S	ESR3	102461	05/08/2023	05/08/2024
Chamber 19	Loop Antenna	EM	EM-6879	271	10/02/2023	10/02/2024
Chamber 19	Bilog Antenna (30MHz-1GHz)	Schwarzbeck	VULB9168 w 6dB Att.	9168-736	03/09/2023	03/09/2024
Chamber 19	Horn antenna (1GHz-18GHz)	ETS-LINDGRE N	3117	00218718	10/04/2023	10/04/2024
Chamber 19	Horn antenna (18GHz-26GHz)	Com-power	AH-826	081001	11/24/2023	11/24/2024
Chamber 19	Horn antenna (26GHz-40GHz)	Com-power	AH-640	100A	03/25/2023	03/25/2024
Chamber 19	Preamplifier (9kHz - 3GHz)	EM	EM330	060822	1/05/2023	1/05/2024
Chamber 19	Preamplifier (1GHz - 26GHz)	HP	8449B	3008A02471	10/25/2023	10/25/2024
Chamber 19	Preamplifier (26GHz-40GHz)	MITEQ	JS4-26004000-27-5A	818471	05/04/2023	05/04/2024
Chamber 19	RF Cable (9kHz-26.5GHz)	Huber Suhner	SUCOFLEX 104A	MY1394/4A&MY 1395/4A	09/06/2023	09/06/2024
Chamber 19	RF Cable (18GHz-40GHz)	HUBER SU-HNER	Sucoflex 102	27963/2&37421/2	11/22/2023	11/22/2024
Chamber 19	Signal Generator	Anritsu	MG3692A	20311	12/29/2022	12/29/2023
Chamber 19	Test Software	Audix	E3 Ver:6.120203b	N/A	N/A	N/A


9.3 Test SET-UP:

9.3.1 Conducted Emission at antenna port:


Refer to section 6.3 for details.

9.3.2 Radiated emission:

(A) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(B) Radiated Emission Test Set-UP Frequency Over 1 GHz



9.4 Measurement Procedure:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = operating frequency.
4. Set the spectrum analyzer as RBW, VBW=100kHz, Span=25MHz, Sweep = auto
5. Mark Peak, 2.390GHz and 2.4835GHz and record the max. level.
6. Repeat above procedures until all frequency measured were complete.

9.5 Field Strength Calculation:

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where	FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
	RA = Reading Amplitude	AG = Amplifier Gain
	AF = Antenna Factor	

9.6 Measurement Result:

Note: Refer to next page spectrum analyzer data chart and tabular data sheets.

10 Peak Power Spectral Density

10.1 Standard Applicable:

According to §15.247(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

According to RSS-247 issue 2, §5.2

(2)The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of Section 5.4(4), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

10.2 Measurement Equipment Used:

Refer to section 6.2 for details.

10.3 Test Set-up:

Refer to section 6.3 for details.


10.4 Measurement Procedure:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW =100kHz, VBW = 300kHz, Span =5 to 30% greater than emission BW, Sweep=Auto
4. Record the max. reading.
5. Repeat above procedures until all frequency measured were complete.


10.5 Measurement Result:

Mode	Frequency (MHz)	PSD (dBm/3kHz)	Duty Factor (dB)	Total PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)
LoRa	902.5	-1.567	-----	-1.567	8.00
	915.5	-1.091	-----	-1.091	8.00
	927.5	-2.552	-----	-2.552	8.00


LoRa Power Spectral Density Test Plot (CH-Low)



Power Spectral Density Test Plot (CH-Mid)



Power Spectral Density Test Plot (CH-High)



11 Antenna Requirement

11.1 Standard Applicable:

According to §15.203, Antenna requirement.

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

According to RSS-GEN 6.8 antenna requirement: The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna.

The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below). When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

<p>This radio transmitter [enter the device's ISSED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.</p>
--

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

11.2 Antenna Connected Construction:

	Antenna Type	Brand	Model	Peak Gain	Frequency Range	Connector Type
1	Dipole	Fanstel	YZ868-915-RPSMA-200	1.46dBi	868-930 MHz	RPSMA
2	Flexible PCB	TE Connectivity	2195835-5	4.50dBi	868-930 MHz	U.FL
3	CHIP	onewave	WAN031003F0391SM03	1.32dBi	898-928 MHz	-----

Appendix 1

Photographs of Set Up


Radiated Emission Setup Photos (below 1G) Config 1





Radiated Emission Setup Photos (above 1G) Config 1






Radiated Emission Setup Photos (below 1G) Config 2






Radiated Emission Setup Photos (above 1G) Config 2








Radiated Emission Setup Photos (below 1G) Config 3







Radiated Emission Setup Photos (above 1G) Config 3





Conducted Emission Setup Photos





Appendix 2

Photographs of EUT

Please refer to the file ISL-23LR0182P-

~ End of Report ~