

Maximum Permissible Exposure (MPE)

Standard Applicable

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

This is a Mobile device, the MPE is required.

According to §1.1310 and §2.1091 RF exposure is calculated.

Limits for Maximum Permissive Exposure (MPE)

| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Averaging Time (minute) |
|---|----------------------------------|----------------------------------|--|----------------------------|
| Limits for General Population/Uncontrolled Exposure | | | | |
| 0.3-1.34 | 614 | 1.63 | *(100) | 30 |
| 1.34-30 | 824/f | 2.19/f | *(180/f ²) | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | / | / | F/1500 | 30 |
| 1500-15000 | / | / | 1.0 | 30 |

F = frequency in MHz

* = Plane-wave equipment power density

According to RSS 102 issue 5.

2.5.2 Exemption Limits for Routine Evaluation – RF Exposure Evaluation

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $22.48/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

Bluetooth Tune-Up Power:

| | |
|--------------------|--|
| Frequency Range: | 2402 – 2480MHz |
| Bluetooth Version: | V5.1 |
| Tune-Up Power | +/- 0.4 dBm |
| Antenna Gain | BT40E (Dipole Ant.): Dipole Antenna, 6dBi BT40F (PCB Ant.): PCB Antenna, 0.88dBi BT40: PCB Antenna, -3.37dBi |

Maximum Permissible Exposure (MPE) Evaluation (BLE)

| Frequency Band (MHz) | Conducted power (dBm) | Antenna gain (dBi) | Tune-Up Tolerance (dB) | EIRP (dBm) | MPE (W/m ²) | LIMIT (W/m ²) |
|----------------------|-----------------------|--------------------|------------------------|------------|-------------------------|---------------------------|
| 2412 - 2462 | 3.383 | 6 | 0.4 | 9.783 | 0.019 | 5.366 |

~ End ~