

TEST REPORT

of

FCC Part 15 Subpart C AND CANADA RSS-247

☒ New Application; ☐ Class I PC; ☐ Class II PC

Product : ESP32 WROOM-32 module
Brand: Fanstel
Model: ESP32M4; ESP32E4; ESP32M16; ESP32E16;
ESP32F16; ESP32F4
Model Difference: Memory , Antenna . Please see page 5 for detail
FCC ID: X8WESP32M16
IC: 4100A-ESP32M16
FCC Rule Part: §15.247, Cat: DTS
IC Rule Part: RSS-247 issue 2: 2017
RSS-Gen issue 5: 2018
Applicant: Fanstel Corporation, Taipei
Address: 10F-10, No. 79, Sec. 1, Hsin Tai Wu Rd.,
Hsi-Chih, New Taipei City 221 Taiwan

Test Performed by:
International Standards Laboratory Corp.

<LT Lab.>

*Site Registration No.

BSMI: SL2-IN-E-0013; MRA TW1036; TAF: 0997; IC: IC4067B-4;

*Address:

No. 120, Lane 180, San Ho Tsuen, Hsin Ho Rd.

Lung-Tan Hsiang, Tao Yuan County 325, Taiwan

*Tel : 886-3-407-1718; Fax: 886-3-407-1738

Report No.: ISL-20LR045FCDTS

Issue Date : 2020/04/17

Test results given in this report apply only to the specific sample(s) tested and are traceable to national or international standard through calibration of the equipment and evaluating measurement uncertainty herein.

This report MUST not be used to claim product endorsement by TAF, NVLAP or any agency of the Government.

This test report shall not be reproduced except in full, without the written approval of International Standards Laboratory Corp.

VERIFICATION OF COMPLIANCE

Applicant: Fanstel Corporation, Taipei
Product Description: ESP32 WROOM-32 module
Brand Name: Fanstel
Model No.: ESP32M4; ESP32E4; ESP32M16; ESP32E16; ESP32F16;
ESP32F4
Model Difference: Memory , Antenna . Please see page 5 for detail
FCC ID: X8WESP32M16
IC: 4100A-ESP32M16
Date of test: 2020/02/20 ~ 2020/04/10
Date of EUT Received: 2020/02/20

We hereby certify that:

All the tests in this report have been performed and recorded in accordance with the standards described above and performed by an independent electromagnetic compatibility consultant, International Standards Laboratory Corp.

The test results contained in this report accurately represent the measurements of the characteristics and the energy generated by sample equipment under test at the time of the test. The sample equipment tested as described in this report is in compliance with the limits of above standards.

Test By: Weitin Chen **Date:** 2020/04/17

Weitin Chen / Senior Engineer

Prepared By: Gigi yeh **Date:** 2020/04/17

Gigi Yeh / Senior Engineer

Approved By: Jerry Liu **Date:** 2020/04/17

Jerry Liu / Technical Manager

Version

Version No.	Date	Description
00	2020/04/17	Initial creation of document

Uncertainty of Measurement

Description Of Test	Uncertainty
Conducted Emission (AC power line)	2.586 dB
Field Strength of Spurious Radiation	$\leq 30\text{MHz}$: 2.96dB 30-1GHz: 4.22 dB 1-40 GHz: 4.08 dB
Conducted Power	2.412 GHz: 1.30 dB
Power Density	2.412 GHz: 1.30 dB
Frequency	0.0032%
Time	0.01%
DC Voltage	1%

Table of Contents

1	General Information.....	7
1.1	Related Submittal(s) / Grant (s)	10
1.2	Test Methodology	10
1.3	Test Facility.....	10
1.4	Special Accessories	10
1.5	Equipment Modifications.....	10
2	SYSTEM TEST CONFIGURATION	11
2.1	EUT Configuration	11
2.2	EUT Exercise	11
2.3	Test Procedure.....	11
2.4	Configuration of Tested System.....	12
3	Summary of Test Results.....	13
4	Description of Test Modes.....	13
5	Conducted Emission Test	14
5.1	Standard Applicable:	14
5.2	Measurement Equipment Used:	14
5.3	EUT Setup:.....	14
5.4	Measurement Procedure:	15
5.5	Measurement Result:	15
6	Peak Output Power Measurement	18
6.1	Standard Applicable:	18
6.2	Measurement Equipment Used:	19
6.3	Test Set-up:	19
6.4	Measurement Procedure:	19
6.5	Measurement Result:	20
7	6dB Bandwidth & 99% Bandwidth	21
7.1	Standard Applicable:	21
7.2	Measurement Equipment Used:	21
7.3	Test Set-up:	21
7.4	Measurement Procedure:	21
7.5	Measurement Result:	22
8	Spurious Radiated Emission Test.....	35
8.1	Standard Applicable	35
8.2	Measurement Equipment Used:	35
8.3	Test SET-UP:.....	35
8.4	Measurement Procedure:	36
8.5	Field Strength Calculation	37
8.6	Measurement Result:	37
9	100kHz Bandwidth of Band Edges Measurement	86
9.1	Standard Applicable:	86
9.2	Measurement Equipment Used:	87
9.3	Test Setup.....	88
9.4	Measurement Procedure:	89
9.5	Field Strength Calculation:	89
9.6	Measurement Result:	89
10	Peak Power Spectral Density	110
10.1	Standard Applicable:	110
10.2	Measurement Equipment Used:	110
10.3	Test Set-up:	110
10.4	Measurement Procedure:	110

10.5	Measurement Result:	111
11	Antenna Requirement	118
11.1	Standard Applicable:	118
11.2	Antenna Connected Construction:	119
PHOTOGRAPHS OF SET UP		120
PHOTOGRAPHS OF EUT		126

1 General Information

General:

Product Name	ESP32 WROOM-32 module
Brand Name	Fanstel
Model Name	ESP32M4; ESP32E4; ESP32M16; ESP32E16; ESP32F16; ESP32F4
Model Difference	Memory , Antenna . Please see page 5 for detail
Power Tolerance:	+/- 1 dB
Power Supply	5Vdc by USB port

Model Summaries

module	ESP32M4	ESP32F4.	ESP32E4.	ESP32M16	ESP32F16	ESP32E16.
SoC	ESP32-D0WD	ESP32-D0WD	ESP32-D0WD	ESP32-D0WD	ESP-D0WD	ESP32-D0WD
Flash memory	4MB, IS25LP032-JBLE	4MB, IS25LP032-JBLE	4MB, IS25LP032-JBLE	16MB, IS25LP128-JBLE	16MB, IS25LP128-JBLE	16MB, IS25LP128-JBLE
Size	18x25.5	18x25.5	18x25.5	18x25.5	20x29.5	18x25.5
WIFI Antenna	PCB trace	PCB trace	u.FL	PCB trace	PCB trace	u.FL
Max TX						
Operating temp.	-40°C to +105°C	-40°C to +105°C	-40°C to +105°C	-40°C to +105°C	-40°C to +105°C	-40°C to +105°C
Price at 1K pcs	\$3.46			\$4.33		\$4.49
Availability				Sample 03/2020		Sample 03/2020

IC RSS-Gen:

PMN (Product Marketing Name)	ESP32M4; ESP32E4; ESP32M16; ESP32E16; ESP32F16; ESP32F4
HVIN (Hardware Version Identification Number)	ESP32M4; ESP32E4; ESP32M16; ESP32E16; ESP32F16; ESP32F4
Product SW version	ESP32-V1
Product HW version	ESP32_RF_TEST_BIN_V1.5.0_20190812
Radio SW version	N/A
Radio HW version	N/A
Test SoftWare Version	ESP_RF_test_tool_v2.3
RF power setting in TEST SoftWare	802.11b setting 0 802.11g setting 20 802.11n20 setting 20 802.11n40 setting 20

2.4GHz WLAN: 1TX/1RX

Wi-Fi	Frequency Range (MHz)	Channels	Peak / Average Power	Modulation Technology
802.11b	2412 – 2462(DTS)	11	23.72dBm (PK)	DSSS
802.11g	2412 – 2462(DTS)	11	23.50dBm (PK)	OFDM
802.11n	HT20 2412 – 2462(DTS)	11	23.98dBm (PK)	
802.11n	HT40 2422 – 2452(DTS)	7	23.53dBm (PK)	
Modulation type		CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM		
Antenna Designation		PCB Antenna ESP32M : 2.22 dBi ESP32F: 1.70 dBi Dipole Antenna ESP32E : 0dBi		

This report applies for 2.4GHz Wifi

Remark: The above DUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.1 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID: X8WESP32M16** filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules and **IC: 4100A-ESP32M16** filing to comply with Industry Canada RSS-247 issue 2.

1.2 Test Methodology

Both conducted and radiated testing were performed according to the procedures in ANSI C63.10: 2013. Radiated testing was performed at an antenna to EUT distance 3 meters.

KDB Document: 558074 D01 15.247 Meas Guidance v05r02

1.3 Test Facility

The measurement facilities used to collect the 3m Radiated Emission and AC power line conducted data are located on the address of **International Standards Laboratory Corp.**<LT Lab.> No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist., Tao Yuan City 325, Taiwan which are constructed and calibrated to meet the FCC requirements in documents ANSI C63.10: 2013. FCC Registration Number is: 487532; Designation Number is: TW0997, Canada Registration Number: 4067B-4.

1.4 Special Accessories

Not available for this EUT intended for grant.

1.5 Equipment Modifications

Not available for this EUT intended for grant.

2 SYSTEM TEST CONFIGURATION

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The EUT (Transmitter) was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements.

2.3 Test Procedure

2.3.1 Conducted Emissions

The EUT is placed on a turn table which is 0.8 m above ground plane. According to the requirements in Section 6 of ANSI C63.10: 2013 and RSS-Gen issue 5. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR 16-1-1 Quasi-Peak and Average detector mode.

2.3.2 Radiated Emissions

The EUT is placed on a turn table which is 0.8 m/1.5m (frequency above 1GHz) above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter(EUT) was rotated through three orthogonal axes according to the requirements in Section 6 and 11 of ANSI C63.10: 2013.

2.4 Configuration of Tested System

Fig. 2-1 Configuration of Tested System (Fixed channel)




Table 2-1 Equipment Used in Tested System

Item	Equip- ment	Mfr/Brand	Model/ Type No.	Series No.	Data Cable	Power Cord
1	NB	Lenovo	X220i	NA	Non-Shielding	Non-Shielding

3 Summary of Test Results

FCC Rules	Description Of Test	Result
§15.207(a) RSS-Gen §8.8	AC Power Line Conducted Emission	Compliant
§15.247(b) (3),(4) RSS-247 issue 2, §5.4(4)	Peak Output Power/ EIRP	Compliant
§15.247(a)(2) RSS-247 issue 2, §5.2(1) RSS-Gen §6.6	6dB & 99% Power Bandwidth	Compliant
§15.247(d) RSS-247 issue 2, §5.5	100 kHz Bandwidth of Frequency Band Edges	Compliant
§15.247(d) RSS-247 issue 2, §5.5	Spurious Emission	Compliant
§15.247(e) RSS-247 issue 2, §5.2	Peak Power Density	Compliant
§15.203 RSS-GEN 8.3	Antenna Requirement	Compliant

4 Description of Test Modes

The EUT has been tested under engineering operating condition.

Test program used to control the EUT for staying in continuous transmitting mode is programmed.

802.11 b mode: Channel low (2412MHz)、mid (2437MHz)、high (2462MHz) with 1Mbps lowest data rate are chosen for full testing.

802.11 g mode: Channel low (2412MHz)、mid (2437MHz)、high (2462MHz) with 6Mbps lowest data rate are chosen for full testing.

802.11 n _20MHz: Channel low (2412MHz)、mid (2437MHz)、high (2462MHz) with 6.5Mbps lowest data rate are chosen for full testing.

802.11 n _40MHz: Channel low (2422MHz)、mid (2437MHz)、high (2452MHz) with 13.5Mbps lowest data rate are chosen for full testing.

5 Conducted Emission Test

5.1 Standard Applicable:

According to §15.207 and RSS-Gen §7.2.4, frequency range within 150kHz to 30MHz shall not exceed the Limit table as below.

Frequency range MHz	Limits dB(uV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50
Note 1.The lower limit shall apply at the transition frequencies 2.The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.		

5.2 Measurement Equipment Used:

Conducted Emission Test Site					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Conduction 04-3 Cable	WOKEN	CFD 300-NL	Conduction 04 -3	08/29/2019	08/29/2020
EMI Receiver 18	Rohde & Schwarz	ESCI	101392	07/25/2019	07/25/2020
LISN 18	ROHDE & SCHWARZ	ENV216	101424	11/06/2019	11/06/2020
LISN 03	ROHDE & SCHWARZ	ESH3-Z5	828874/010	08/13/2019	08/13/2020
Test Software	Farad	EZEMC Ver:ISL-03A2	N/A	N/A	N/A

5.3 EUT Setup:

1. The conducted emission tests were performed in the test site, using the setup in accordance with the ANSI C63.10-2013.
2. The AC/DC Power adaptor of EUT was plug-in LISN. The EUT was placed flushed with the rear of the table.
3. The LISN was connected with 120Vac/60Hz power source.

5.4 Measurement Procedure:

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.
4. Both 120V & 240V have been verified, and 120V/60Hz was defined as the worst-case and record in the report.

5.5 Measurement Result:

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

Note: Refer to next page for measurement data and plots.

AC POWER LINE CONDUCTED EMISSION TEST DATA

Operation Mode:	Full mode	Test Date:	2020/03/19
Test By:	Weitin		



Address: No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
Tao Yuan City 325, Taiwan.
Tel: 03-4071718


Conducted Emission Measurement

Date: 2020/3/19

operator: Kevin Chan

Temperature: 26 °C

Humidity: 60 %



Site: Conduction 02

Phase: L1

No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	0.462	29.22	17.41	9.69	38.91	56.66	-17.75	27.10	46.66	-19.56
2	0.510	29.96	16.73	9.70	39.66	56.00	-16.34	26.43	46.00	-19.57
3	0.890	15.25	3.39	9.71	24.96	56.00	-31.04	13.10	46.00	-32.90
4	1.126	28.41	14.00	9.71	38.12	56.00	-17.88	23.71	46.00	-22.29
5	1.290	24.74	12.12	9.72	34.46	56.00	-21.54	21.84	46.00	-24.16
6	5.858	26.28	12.74	9.84	36.12	60.00	-23.88	22.58	50.00	-27.42
7	7.494	24.79	12.20	9.87	34.66	60.00	-25.34	22.07	50.00	-27.93
8	10.582	26.13	16.71	9.93	36.06	60.00	-23.94	26.64	50.00	-23.36



Address: No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
Tao Yuan City 325, Taiwan.
Tel: 03-4071718


Conducted Emission Measurement

Date: 2020/3/19

operator: Kevin Chan

Temperature: 26 °C

Humidity: 60 %



Site: Conduction 02

Phase: N

No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	0.474	38.93	27.50	9.68	48.61	56.44	-7.83	37.18	46.44	-9.26
2	0.498	35.63	24.44	9.69	45.32	56.03	-10.71	34.13	46.03	-11.90
3	0.546	36.98	28.52	9.69	46.67	56.00	-9.33	38.21	46.00	-7.79
4	0.566	34.30	22.64	9.69	43.99	56.00	-12.01	32.33	46.00	-13.67
5	0.662	27.94	15.36	9.69	37.63	56.00	-18.37	25.05	46.00	-20.95
6	1.038	28.01	18.44	9.70	37.71	56.00	-18.29	28.14	46.00	-17.86
7	2.170	23.81	13.54	9.75	33.56	56.00	-22.44	23.29	46.00	-22.71
8	4.910	25.05	15.66	9.82	34.87	56.00	-21.13	25.48	46.00	-20.52
9	9.050	29.50	19.85	9.92	39.42	60.00	-20.58	29.77	50.00	-20.23
10	9.902	28.83	19.02	9.94	38.77	60.00	-21.23	28.96	50.00	-21.04

6 Peak Output Power Measurement

6.1 Standard Applicable:

According to §15.247(b)(3),(4)(b)

(3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(c) Operation with directional antenna gains greater than 6 dBi.

(1) Fixed point-to-point operation:

(i) Systems operating in the 2400-2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

(ii) Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted output power.

According to RSS-247 issue 2, §5.4


(D)For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e)

As an alternative to a peak power measurement, compliance can be based on a measurement of the maximum conducted output power. The maximum conducted output power is the total transmit power delivered to all antennas and antenna elements, averaged across all symbols in the signalling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or transmitting at a reduced power level. If multiple modes of operation are implemented, the maximum conducted output power is the highest total transmit power occurring in any mode.

6.2 Measurement Equipment Used:

Location Conducted	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Conducted	Power Meter	Anritsu	ML2495A	1116010	10/04/2019	10/04/2020
Conducted	Power Sensor	Anritsu	MA2411B	34NKF50	10/04/2019	10/04/2020
Conducted	Power Sensor	DARE	RPR3006W	13I00030SNO33	01/03/2020	01/03/2021
Conducted	Power Sensor	DARE	RPR3006W	13I00030SNO34	01/09/2020	01/09/2021
Conducted	Power Sensor	DARE	RPR3006W	14I00889SNO35	06/27/2019	06/27/2020
Conducted	Power Sensor	DARE	RPR3006W	14I00889SNO36	06/27/2019	06/27/2020
Conducted	Temperature Chamber	KSON	THS-B4H100	2287	03/11/2020	03/11/2021
Conducted	DC Power supply	ABM	8185D	N/A	01/03/2020	01/03/2021
Conducted	AC Power supply	EXTECH	CFC105W	NA	N/A	N/A
Conducted	Spectrum analyzer	Keysight	N9010A	MY56070257	10/05/2019	10/05/2020
Conducted	Spectrum analyzer	R&S	FSP40	100116	01/10/2020	01/10/2021
Conducted	Test Software	DARE	Radiation Ver:2013.1.23	NA	NA	NA
Conducted	Test Software	R&S	CMUGO Ver:2.0.0	N/A	N/A	N/A
Conducted	Radio Communication Analyzer	R&S	CMU200	111968	11/29/2019	11/29/2020
Conducted	Radio Communication Analyzer	R&S	CMW500	1201.002K50108793-JG	10/11/2019	10/11/2020
Conducted	BT Simulator	Agilent	N4010A	MY48100200	NA	NA
Conducted	GPS Simulator	Welnavigate	GS-50	701523	NA	NA

6.3 Test Set-up:



6.4 Measurement Procedure:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power meter
3. Record the max. reading.
4. Repeat above procedures until all frequency measured were complete.

6.5 Measurement Result:

802.11b

Cable loss = 0	Output Power		Limit (dBm)
CH	Detector		
	PK (dBm)	AV (dBm)	
Low	23.72	21.39	30.00
Mid	23.47	20.95	
High	23.29	20.61	

802.11g

Cable loss = 0	Output Power		Limit (dBm)
CH	Detector		
	PK (dBm)	AV (dBm)	
Low	23.50	18.17	30.00
Mid	23.27	17.70	
High	23.03	17.24	

802.11n_HT20

Cable loss = 0	Output Power		Limit (dBm)
CH	Detector		
	PK (dBm)	AV (dBm)	
Low	23.98	18.17	30.00
Mid	23.87	17.81	
High	23.46	17.07	

802.11n_HT40

Cable loss = 0	Output Power		Limit (dBm)
CH	Detector		
	PK (dBm)	AV (dBm)	
Low	23.53	18.09	30.00
Mid	23.37	17.83	
High	23.28	17.64	

7 6dB Bandwidth & 99% Bandwidth

7.1 Standard Applicable:

According to §15.247(a)(2), Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500kHz.


According to RSS-247 issue 2, §5.2

(a)The minimum 6 dB bandwidth shall be 500 kHz.

7.2 Measurement Equipment Used:

Refer to section 6.2 for details.

7.3 Test Set-up:



7.4 Measurement Procedure:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW=100kHz, VBW = 3*RBW, Span= cover the complete power envelope of the signal of the UUT Sweep=auto
4. Mark the peak frequency and -6dB (upper and lower) frequency.
5. Repeat above procedures until all frequency measured were complete.

7.5 Measurement Result:

802.11b

Frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (kHz)	Result
Low	10.12	13.18	> 500	PASS
Mid	10.11	13.07	> 500	PASS
High	10.10	13.00	> 500	PASS

802.11g

Frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (kHz)	Result
Low	16.44	16.46	> 500	PASS
Mid	16.44	16.46	> 500	PASS
High	16.44	16.46	> 500	PASS

802.11n HT20

Frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (kHz)	Result
Low	17.33	17.32	> 500	PASS
Mid	17.34	17.32	> 500	PASS
High	17.34	17.32	> 500	PASS


802.11n HT40

Frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (kHz)	Result
Low	36.45	36.18	> 500	PASS
Mid	36.45	36.16	> 500	PASS
High	36.44	36.18	> 500	PASS


Note: Refer to next page for plots.

802.11b


6dB Bandwidth Test Data CH-Low



6dB Bandwidth Test Data CH-Mid




6dB Bandwidth Test Data CH-High




802.11g


6dB Bandwidth Test Data CH-Low



6dB Bandwidth Test Data CH-Mid




6dB Bandwidth Test Data CH-High




802.11n_HT20


6dB Bandwidth Test Data CH-Low



6dB Bandwidth Test Data CH-Mid




6dB Bandwidth Test Data CH-High




802.11n_HT40


6dB Bandwidth Test Data CH-Low



6dB Bandwidth Test Data CH-Mid




6dB Bandwidth Test Data CH-High




802.11b


99% Occupied Bandwidth Test Data CH-Low



99% Occupied Bandwidth Test Data CH-Mid




99% Occupied Bandwidth Test Data CH-High




802.11g


99% Occupied Bandwidth Test Data CH-Low



99% Occupied Bandwidth Test Data CH-Mid




99% Occupied Bandwidth Test Data CH-High




802.11n_HT20


99% Occupied Bandwidth Test Data CH-Low



99% Occupied Bandwidth Test Data CH-Mid




99% Occupied Bandwidth Test Data CH-High




802.11n_HT40


99% Occupied Bandwidth Test Data CH-Low



99% Occupied Bandwidth Test Data CH-Mid



99% Occupied Bandwidth Test Data CH-High



8 Spurious Radiated Emission Test

8.1 Standard Applicable

According to §15.247(d), all other emissions outside these bands shall not exceed the general radiated emission limits specified in §15.209(a). And according to §15.33(a)(1), for an intentional radiator operates below 10GHz, the frequency range of measurements: to the tenth harmonic of the highest fundamental frequency or to 40GHz, whichever is lower.

According to RSS-247 issue 2, §5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

8.2 Measurement Equipment Used:

8.2.1 Conducted Emission at antenna port:

Refer to section 6.2 for details.

8.2.2 Radiated emission:

Refer to section 8.2 for details.

8.3 Test SET-UP:

The test item only performed radiated mode

Refer to section 8.3 for details.

8.4 Measurement Procedure:

- 1 According 414788 section 2, Either OATS or chamber for radiated emission below 30MHz, the test was done at 966 chamber, the test site was evaluated with OATS and the Chamber has test signals level greater than OATS's.
- 2 The EUT was placed on a turn table which is 0.8m/1.5m above ground plane in 966 chamber.
- 3 The turn table shall rotate 360 degrees to determine the position of maximum emission level.
- 4 EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emissions.
- 5 When measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made "while keeping the antenna in the 'cone of radiation' from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response." is still within the 3dB illumination BW of the measurement antenna.
- 6 Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 7 And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 8 Repeat above procedures until all frequency measured were complete.

Test receiver setting : Blew 1GHz
 Detector : Average(9kHz – 90kHz, 110kHz – 90kHz), Quasi-Peak
 Bandwidth : 200Hz, 120kHz
 Test spectrum setting : Above 1GHz
 Peak : RBW=1MHz, VBW=3MHz, Sweep=auto
 Average (for Wi-Fi) : RBW=1MHz, VBW=10Hz, Sweep=auto

Average Measurement Setting (VBW)

Mode	Duty Cycle (%)	T _{on} (us)	T _{off} (us)	1/T _{on} (kHz)	Determined VBW Setting
802.11b	100	-	-	-	10Hz (Duty cycle ≥ 98%)
802.11g	100	-	-	-	10Hz (Duty cycle ≥ 98%)
802.11n (HT20)	100	-	-	-	10Hz (Duty cycle ≥ 98%)
802.11n (HT40)	100	-	-	-	10Hz (Duty cycle ≥ 98%)

8.5 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where	FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
	RA = Reading Amplitude	AG = Amplifier Gain
	AF = Antenna Factor	

8.6 Measurement Result:

Note: Refer to next page spectrum analyzer data chart and tabular data sheets.

Dipole Antenna

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode	802.11b TX mode	Test Date	2020/03/19
Channel number	CH Low	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	73.65	42.53	-8.58	33.95	40.00	-6.05	Peak	VERTICAL
2	119.24	41.33	-7.81	33.52	43.50	-9.98	Peak	VERTICAL
3	296.75	38.50	-3.99	34.51	46.00	-11.49	Peak	VERTICAL
4	480.08	35.19	-0.85	34.34	46.00	-11.66	Peak	VERTICAL
5	668.26	33.42	2.21	35.63	46.00	-10.37	Peak	VERTICAL
6	740.04	32.99	3.69	36.68	46.00	-9.32	Peak	VERTICAL
1	73.65	47.10	-8.58	38.52	40.00	-1.48	Peak	HORIZONTAL
2	227.88	40.83	-6.89	33.94	46.00	-12.06	Peak	HORIZONTAL
3	335.55	44.45	-3.07	41.38	46.00	-4.62	Peak	HORIZONTAL
4	480.08	36.72	-0.85	35.87	46.00	-10.13	Peak	HORIZONTAL
5	517.91	35.57	-0.27	35.30	46.00	-10.70	Peak	HORIZONTAL
6	813.76	31.86	4.70	36.56	46.00	-9.44	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9kHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode	802.11b TX mode	Test Date	2020/03/19
Channel number	CH Mid	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	73.65	43.76	-8.58	35.18	40.00	-4.82	Peak	VERTICAL
2	119.24	41.71	-7.81	33.90	43.50	-9.60	Peak	VERTICAL
3	295.78	41.51	-4.00	37.51	46.00	-8.49	Peak	VERTICAL
4	336.52	39.47	-3.08	36.39	46.00	-9.61	Peak	VERTICAL
5	455.83	35.64	-1.06	34.58	46.00	-11.42	Peak	VERTICAL
6	665.35	34.52	2.19	36.71	46.00	-9.29	Peak	VERTICAL
1	73.65	45.98	-8.58	37.40	40.00	-2.60	Peak	HORIZONTAL
2	173.56	39.19	-5.47	33.72	43.50	-9.78	Peak	HORIZONTAL
3	335.55	43.03	-3.07	39.96	46.00	-6.04	Peak	HORIZONTAL
4	480.08	35.47	-0.85	34.62	46.00	-11.38	Peak	HORIZONTAL
5	597.45	36.79	1.38	38.17	46.00	-7.83	Peak	HORIZONTAL
6	816.67	31.42	4.80	36.22	46.00	-9.78	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9kHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode	802.11b TX mode	Test Date	2020/03/19
Channel number	CH High	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	73.65	42.07	-8.58	33.49	40.00	-6.51	Peak	VERTICAL
2	119.24	41.02	-7.81	33.21	43.50	-10.29	Peak	VERTICAL
3	333.61	39.75	-3.10	36.65	46.00	-9.35	Peak	VERTICAL
4	455.83	34.40	-1.06	33.34	46.00	-12.66	Peak	VERTICAL
5	668.26	35.37	2.21	37.58	46.00	-8.42	Peak	VERTICAL
6	740.04	32.31	3.69	36.00	46.00	-10.00	Peak	VERTICAL
1	73.65	45.37	-8.58	36.79	40.00	-3.21	Peak	HORIZONTAL
2	171.62	39.11	-5.22	33.89	43.50	-9.61	Peak	HORIZONTAL
3	323.91	45.76	-3.46	42.30	46.00	-3.70	Peak	HORIZONTAL
4	480.08	35.57	-0.85	34.72	46.00	-11.28	Peak	HORIZONTAL
5	519.85	36.02	-0.19	35.83	46.00	-10.17	Peak	HORIZONTAL
6	817.64	32.94	4.85	37.79	46.00	-8.21	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9kHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode	802.11g TX mode	Test Date	2020/03/19
Channel number	CH Low	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	73.65	41.74	-8.58	33.16	40.00	-6.84	Peak	VERTICAL
2	119.24	41.33	-7.81	33.52	43.50	-9.98	Peak	VERTICAL
3	323.91	44.15	-3.46	40.69	46.00	-5.31	Peak	VERTICAL
4	480.08	34.83	-0.85	33.98	46.00	-12.02	Peak	VERTICAL
5	666.32	35.27	2.20	37.47	46.00	-8.53	Peak	VERTICAL
6	742.95	31.80	3.76	35.56	46.00	-10.44	Peak	VERTICAL
1	73.65	47.51	-8.58	38.93	40.00	-1.07	Peak	HORIZONTAL
2	175.50	39.68	-5.69	33.99	43.50	-9.51	Peak	HORIZONTAL
3	335.55	42.32	-3.07	39.25	46.00	-6.75	Peak	HORIZONTAL
4	480.08	36.79	-0.85	35.94	46.00	-10.06	Peak	HORIZONTAL
5	640.13	33.14	1.92	35.06	46.00	-10.94	Peak	HORIZONTAL
6	813.76	33.61	4.70	38.31	46.00	-7.69	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9kHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode	802.11g TX mode	Test Date	2020/03/19
Channel number	CH Mid	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	73.65	41.88	-8.58	33.30	40.00	-6.70	Peak	VERTICAL
2	119.24	41.00	-7.81	33.19	43.50	-10.31	Peak	VERTICAL
3	175.50	36.96	-5.69	31.27	43.50	-12.23	Peak	VERTICAL
4	333.61	37.35	-3.10	34.25	46.00	-11.75	Peak	VERTICAL
5	480.08	35.03	-0.85	34.18	46.00	-11.82	Peak	VERTICAL
6	668.26	35.39	2.21	37.60	46.00	-8.40	Peak	VERTICAL
1	73.65	46.83	-8.58	38.25	40.00	-1.75	Peak	HORIZONTAL
2	173.56	39.37	-5.47	33.90	43.50	-9.60	Peak	HORIZONTAL
3	335.55	42.77	-3.07	39.70	46.00	-6.30	Peak	HORIZONTAL
4	480.08	35.67	-0.85	34.82	46.00	-11.18	Peak	HORIZONTAL
5	591.63	33.07	1.21	34.28	46.00	-11.72	Peak	HORIZONTAL
6	817.64	31.56	4.85	36.41	46.00	-9.59	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9kHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode	802.11g TX mode	Test Date	2020/03/19
Channel number	CH High	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	73.65	42.71	-8.58	34.13	40.00	-5.87	Peak	VERTICAL
2	119.24	41.25	-7.81	33.44	43.50	-10.06	Peak	VERTICAL
3	175.50	37.09	-5.69	31.40	43.50	-12.10	Peak	VERTICAL
4	333.61	39.20	-3.10	36.10	46.00	-9.90	Peak	VERTICAL
5	517.91	33.32	-0.27	33.05	46.00	-12.95	Peak	VERTICAL
6	668.26	36.30	2.21	38.51	46.00	-7.49	Peak	VERTICAL
1	74.62	44.92	-8.71	36.21	40.00	-3.79	Peak	HORIZONTAL
2	168.71	38.42	-5.06	33.36	43.50	-10.14	Peak	HORIZONTAL
3	320.03	42.39	-3.60	38.79	46.00	-7.21	Peak	HORIZONTAL
4	480.08	35.44	-0.85	34.59	46.00	-11.41	Peak	HORIZONTAL
5	559.62	33.51	0.36	33.87	46.00	-12.13	Peak	HORIZONTAL
6	817.64	30.91	4.85	35.76	46.00	-10.24	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9kHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode	802.11n HT20 TX mode	Test Date	2020/03/19
Channel number	CH Low	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	73.65	42.29	-8.58	33.71	40.00	-6.29	Peak	VERTICAL
2	119.24	40.75	-7.81	32.94	43.50	-10.56	Peak	VERTICAL
3	333.61	37.82	-3.10	34.72	46.00	-11.28	Peak	VERTICAL
4	504.33	34.46	-0.53	33.93	46.00	-12.07	Peak	VERTICAL
5	668.26	33.92	2.21	36.13	46.00	-9.87	Peak	VERTICAL
6	740.04	31.29	3.69	34.98	46.00	-11.02	Peak	VERTICAL
1	73.65	47.19	-8.58	38.61	40.00	-1.39	Peak	HORIZONTAL
2	175.50	40.33	-5.69	34.64	43.50	-8.86	Peak	HORIZONTAL
3	339.43	43.66	-3.09	40.57	46.00	-5.43	Peak	HORIZONTAL
4	480.08	35.83	-0.85	34.98	46.00	-11.02	Peak	HORIZONTAL
5	582.90	35.61	0.98	36.59	46.00	-9.41	Peak	HORIZONTAL
6	813.76	32.35	4.70	37.05	46.00	-8.95	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9kHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode	802.11n HT20 TX mode	Test Date	2020/03/19
Channel number	CH Mid	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	73.65	43.85	-8.58	35.27	40.00	-4.73	Peak	VERTICAL
2	119.24	41.30	-7.81	33.49	43.50	-10.01	Peak	VERTICAL
3	300.63	42.25	-3.96	38.29	46.00	-7.71	Peak	VERTICAL
4	332.64	38.66	-3.11	35.55	46.00	-10.45	Peak	VERTICAL
5	508.21	36.65	-0.49	36.16	46.00	-9.84	Peak	VERTICAL
6	665.35	33.59	2.19	35.78	46.00	-10.22	Peak	VERTICAL
1	73.65	45.41	-8.58	36.83	40.00	-3.17	Peak	HORIZONTAL
2	167.74	38.47	-5.00	33.47	43.50	-10.03	Peak	HORIZONTAL
3	332.64	43.72	-3.11	40.61	46.00	-5.39	Peak	HORIZONTAL
4	517.91	35.54	-0.27	35.27	46.00	-10.73	Peak	HORIZONTAL
5	579.99	37.70	0.97	38.67	46.00	-7.33	Peak	HORIZONTAL
6	813.76	31.09	4.70	35.79	46.00	-10.21	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9kHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

1.

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode	802.11n HT20 TX mode	Test Date	2020/03/19
Channel number	CH High	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	73.65	41.69	-8.58	33.11	40.00	-6.89	Peak	VERTICAL
2	119.24	41.38	-7.81	33.57	43.50	-9.93	Peak	VERTICAL
3	296.75	39.56	-3.99	35.57	46.00	-10.43	Peak	VERTICAL
4	333.61	37.04	-3.10	33.94	46.00	-12.06	Peak	VERTICAL
5	480.08	34.96	-0.85	34.11	46.00	-11.89	Peak	VERTICAL
6	666.32	34.68	2.20	36.88	46.00	-9.12	Peak	VERTICAL
1	73.65	46.31	-8.58	37.73	40.00	-2.27	Peak	HORIZONTAL
2	167.74	38.51	-5.00	33.51	43.50	-9.99	Peak	HORIZONTAL
3	335.55	42.61	-3.07	39.54	46.00	-6.46	Peak	HORIZONTAL
4	519.85	34.84	-0.19	34.65	46.00	-11.35	Peak	HORIZONTAL
5	591.63	33.80	1.21	35.01	46.00	-10.99	Peak	HORIZONTAL
6	813.76	31.73	4.70	36.43	46.00	-9.57	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9kHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode	802.11n HT40 TX mode	Test Date	2020/03/19
Channel number	CH Low	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	119.24	40.93	-7.81	33.12	43.50	-10.38	Peak	VERTICAL
2	175.50	37.99	-5.69	32.30	43.50	-11.20	Peak	VERTICAL
3	332.64	38.14	-3.11	35.03	46.00	-10.97	Peak	VERTICAL
4	369.50	36.45	-2.56	33.89	46.00	-12.11	Peak	VERTICAL
5	480.08	34.84	-0.85	33.99	46.00	-12.01	Peak	VERTICAL
6	666.32	34.71	2.20	36.91	46.00	-9.09	Peak	VERTICAL
1	73.65	43.48	-8.58	34.90	40.00	-5.10	Peak	HORIZONTAL
2	173.56	40.48	-5.47	35.01	43.50	-8.49	Peak	HORIZONTAL
3	295.78	39.04	-4.00	35.04	46.00	-10.96	Peak	HORIZONTAL
4	335.55	42.27	-3.07	39.20	46.00	-6.80	Peak	HORIZONTAL
5	480.08	36.29	-0.85	35.44	46.00	-10.56	Peak	HORIZONTAL
6	518.88	35.97	-0.23	35.74	46.00	-10.26	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9kHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode	802.11n HT40 TX mode	Test Date	2020/03/19
Channel number	CH Mid	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	119.24	41.41	-7.81	33.60	43.50	-9.90	Peak	VERTICAL
2	177.44	37.15	-5.96	31.19	43.50	-12.31	Peak	VERTICAL
3	333.61	38.44	-3.10	35.34	46.00	-10.66	Peak	VERTICAL
4	455.83	34.91	-1.06	33.85	46.00	-12.15	Peak	VERTICAL
5	594.54	30.67	1.28	31.95	46.00	-14.05	Peak	VERTICAL
6	668.26	34.32	2.21	36.53	46.00	-9.47	Peak	VERTICAL
1	73.65	45.86	-8.58	37.28	40.00	-2.72	Peak	HORIZONTAL
2	171.62	39.21	-5.22	33.99	43.50	-9.51	Peak	HORIZONTAL
3	333.61	43.86	-3.10	40.76	46.00	-5.24	Peak	HORIZONTAL
4	408.30	38.02	-1.94	36.08	46.00	-9.92	Peak	HORIZONTAL
5	519.85	34.56	-0.19	34.37	46.00	-11.63	Peak	HORIZONTAL
6	640.13	32.43	1.92	34.35	46.00	-11.65	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9kHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode	802.11n HT40 TX mode	Test Date	2020/03/19
Channel number	CH High	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	119.24	41.41	-7.81	33.60	43.50	-9.90	Peak	VERTICAL
2	177.44	37.45	-5.96	31.49	43.50	-12.01	Peak	VERTICAL
3	333.61	38.29	-3.10	35.19	46.00	-10.81	Peak	VERTICAL
4	455.83	34.65	-1.06	33.59	46.00	-12.41	Peak	VERTICAL
5	667.29	34.68	2.21	36.89	46.00	-9.11	Peak	VERTICAL
6	740.04	34.16	3.69	37.85	46.00	-8.15	Peak	VERTICAL
1	73.65	46.37	-8.58	37.79	40.00	-2.21	Peak	HORIZONTAL
2	169.68	39.39	-5.08	34.31	43.50	-9.19	Peak	HORIZONTAL
3	336.52	45.86	-3.08	42.78	46.00	-3.22	Peak	HORIZONTAL
4	517.91	36.56	-0.27	36.29	46.00	-9.71	Peak	HORIZONTAL
5	591.63	33.99	1.21	35.20	46.00	-10.80	Peak	HORIZONTAL
6	816.67	31.48	4.80	36.28	46.00	-9.72	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9kHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

PIFA Antenna

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode	802.11b TX mode	Test Date	2020/03/19
Channel number	CH Low	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	73.65	42.52	-8.58	33.94	40.00	-6.06	Peak	VERTICAL
2	119.24	41.26	-7.81	33.45	43.50	-10.05	Peak	VERTICAL
3	167.74	36.31	-5.00	31.31	43.50	-12.19	Peak	VERTICAL
4	333.61	38.15	-3.10	35.05	46.00	-10.95	Peak	VERTICAL
5	480.08	34.65	-0.85	33.80	46.00	-12.20	Peak	VERTICAL
6	666.32	34.09	2.20	36.29	46.00	-9.71	Peak	VERTICAL
1	73.65	45.90	-8.58	37.32	40.00	-2.68	Peak	HORIZONTAL
2	175.50	39.08	-5.69	33.39	43.50	-10.11	Peak	HORIZONTAL
3	339.43	43.10	-3.09	40.01	46.00	-5.99	Peak	HORIZONTAL
4	480.08	36.21	-0.85	35.36	46.00	-10.64	Peak	HORIZONTAL
5	591.63	32.34	1.21	33.55	46.00	-12.45	Peak	HORIZONTAL
6	740.04	33.35	3.69	37.04	46.00	-8.96	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9kHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode	802.11b TX mode	Test Date	2020/03/19
Channel number	CH Mid	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	73.65	43.86	-8.58	35.28	40.00	-4.72	Peak	VERTICAL
2	119.24	41.77	-7.81	33.96	43.50	-9.54	Peak	VERTICAL
3	175.50	37.32	-5.69	31.63	43.50	-11.87	Peak	VERTICAL
4	323.91	42.16	-3.46	38.70	46.00	-7.30	Peak	VERTICAL
5	455.83	34.21	-1.06	33.15	46.00	-12.85	Peak	VERTICAL
6	666.32	34.04	2.20	36.24	46.00	-9.76	Peak	VERTICAL
1	73.65	45.69	-8.58	37.11	40.00	-2.89	Peak	HORIZONTAL
2	173.56	39.01	-5.47	33.54	43.50	-9.96	Peak	HORIZONTAL
3	336.52	43.24	-3.08	40.16	46.00	-5.84	Peak	HORIZONTAL
4	480.08	35.73	-0.85	34.88	46.00	-11.12	Peak	HORIZONTAL
5	579.99	33.70	0.97	34.67	46.00	-11.33	Peak	HORIZONTAL
6	816.67	32.35	4.80	37.15	46.00	-8.85	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9kHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode	802.11b TX mode	Test Date	2020/03/19
Channel number	CH High	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	119.24	41.30	-7.81	33.49	43.50	-10.01	Peak	VERTICAL
2	240.49	40.41	-5.93	34.48	46.00	-11.52	Peak	VERTICAL
3	333.61	38.90	-3.10	35.80	46.00	-10.20	Peak	VERTICAL
4	455.83	35.15	-1.06	34.09	46.00	-11.91	Peak	VERTICAL
5	666.32	36.74	2.20	38.94	46.00	-7.06	Peak	VERTICAL
6	742.95	32.62	3.76	36.38	46.00	-9.62	Peak	VERTICAL
1	73.65	47.01	-8.58	38.43	40.00	-1.57	Peak	HORIZONTAL
2	173.56	39.08	-5.47	33.61	43.50	-9.89	Peak	HORIZONTAL
3	306.45	43.32	-3.79	39.53	46.00	-6.47	Peak	HORIZONTAL
4	480.08	35.97	-0.85	35.12	46.00	-10.88	Peak	HORIZONTAL
5	594.54	33.49	1.28	34.77	46.00	-11.23	Peak	HORIZONTAL
6	817.64	31.11	4.85	35.96	46.00	-10.04	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9kHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode	802.11g TX mode	Test Date	2020/03/19
Channel number	CH Low	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	73.65	43.06	-8.58	34.48	40.00	-5.52	Peak	VERTICAL
2	119.24	41.45	-7.81	33.64	43.50	-9.86	Peak	VERTICAL
3	333.61	37.05	-3.10	33.95	46.00	-12.05	Peak	VERTICAL
4	480.08	34.51	-0.85	33.66	46.00	-12.34	Peak	VERTICAL
5	666.32	33.63	2.20	35.83	46.00	-10.17	Peak	VERTICAL
6	741.01	32.92	3.71	36.63	46.00	-9.37	Peak	VERTICAL
1	73.65	46.67	-8.58	38.09	40.00	-1.91	Peak	HORIZONTAL
2	175.50	39.12	-5.69	33.43	43.50	-10.07	Peak	HORIZONTAL
3	300.63	47.01	-3.96	43.05	46.00	-2.95	Peak	HORIZONTAL
4	332.64	42.21	-3.11	39.10	46.00	-6.90	Peak	HORIZONTAL
5	519.85	35.60	-0.19	35.41	46.00	-10.59	Peak	HORIZONTAL
6	593.57	33.34	1.26	34.60	46.00	-11.40	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9kHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode	802.11g TX mode	Test Date	2020/03/19
Channel number	CH Mid	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	73.65	42.98	-8.58	34.40	40.00	-5.60	Peak	VERTICAL
2	119.24	41.03	-7.81	33.22	43.50	-10.28	Peak	VERTICAL
3	177.44	37.07	-5.96	31.11	43.50	-12.39	Peak	VERTICAL
4	296.75	39.58	-3.99	35.59	46.00	-10.41	Peak	VERTICAL
5	369.50	35.95	-2.56	33.39	46.00	-12.61	Peak	VERTICAL
6	668.26	34.77	2.21	36.98	46.00	-9.02	Peak	VERTICAL
1	73.65	47.54	-8.58	38.96	40.00	-1.04	Peak	HORIZONTAL
2	143.49	39.30	-5.25	34.05	43.50	-9.45	Peak	HORIZONTAL
3	320.03	42.58	-3.60	38.98	46.00	-7.02	Peak	HORIZONTAL
4	408.30	35.92	-1.94	33.98	46.00	-12.02	Peak	HORIZONTAL
5	519.85	35.18	-0.19	34.99	46.00	-11.01	Peak	HORIZONTAL
6	640.13	33.63	1.92	35.55	46.00	-10.45	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9kHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode	802.11g TX mode	Test Date	2020/03/19
Channel number	CH High	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	119.24	41.47	-7.81	33.66	43.50	-9.84	Peak	VERTICAL
2	177.44	37.26	-5.96	31.30	43.50	-12.20	Peak	VERTICAL
3	295.78	39.31	-4.00	35.31	46.00	-10.69	Peak	VERTICAL
4	330.70	39.23	-3.14	36.09	46.00	-9.91	Peak	VERTICAL
5	455.83	35.49	-1.06	34.43	46.00	-11.57	Peak	VERTICAL
6	668.26	33.34	2.21	35.55	46.00	-10.45	Peak	VERTICAL
1	73.65	47.43	-8.58	38.85	40.00	-1.15	Peak	HORIZONTAL
2	173.56	40.14	-5.47	34.67	43.50	-8.83	Peak	HORIZONTAL
3	320.03	42.87	-3.60	39.27	46.00	-6.73	Peak	HORIZONTAL
4	407.33	35.19	-1.96	33.23	46.00	-12.77	Peak	HORIZONTAL
5	519.85	36.94	-0.19	36.75	46.00	-9.25	Peak	HORIZONTAL
6	591.63	34.67	1.21	35.88	46.00	-10.12	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9kHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode	802.11n HT20 TX mode	Test Date	2020/03/19
Channel number	CH Low	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	119.24	41.59	-7.81	33.78	43.50	-9.72	Peak	VERTICAL
2	175.50	36.20	-5.69	30.51	43.50	-12.99	Peak	VERTICAL
3	327.79	38.37	-3.26	35.11	46.00	-10.89	Peak	VERTICAL
4	455.83	34.92	-1.06	33.86	46.00	-12.14	Peak	VERTICAL
5	668.26	34.49	2.21	36.70	46.00	-9.30	Peak	VERTICAL
6	740.04	34.03	3.69	37.72	46.00	-8.28	Peak	VERTICAL
1	73.65	46.78	-8.58	38.20	40.00	-1.80	Peak	HORIZONTAL
2	171.62	38.06	-5.22	32.84	43.50	-10.66	Peak	HORIZONTAL
3	335.55	41.91	-3.07	38.84	46.00	-7.16	Peak	HORIZONTAL
4	408.30	35.70	-1.94	33.76	46.00	-12.24	Peak	HORIZONTAL
5	519.85	34.09	-0.19	33.90	46.00	-12.10	Peak	HORIZONTAL
6	640.13	32.26	1.92	34.18	46.00	-11.82	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9kHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode	802.11n HT20 TX mode	Test Date	2020/03/19
Channel number	CH Mid	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	73.65	41.86	-8.58	33.28	40.00	-6.72	Peak	VERTICAL
2	175.50	36.44	-5.69	30.75	43.50	-12.75	Peak	VERTICAL
3	323.91	39.34	-3.46	35.88	46.00	-10.12	Peak	VERTICAL
4	455.83	34.93	-1.06	33.87	46.00	-12.13	Peak	VERTICAL
5	666.32	33.30	2.20	35.50	46.00	-10.50	Peak	VERTICAL
6	740.04	33.10	3.69	36.79	46.00	-9.21	Peak	VERTICAL
1	73.65	47.00	-8.58	38.42	40.00	-1.58	Peak	HORIZONTAL
2	173.56	39.17	-5.47	33.70	43.50	-9.80	Peak	HORIZONTAL
3	336.52	46.32	-3.08	43.24	46.00	-2.76	Peak	HORIZONTAL
4	517.91	36.10	-0.27	35.83	46.00	-10.17	Peak	HORIZONTAL
5	593.57	32.95	1.26	34.21	46.00	-11.79	Peak	HORIZONTAL
6	813.76	33.15	4.70	37.85	46.00	-8.15	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9kHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

1.

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode	802.11n HT20 TX mode	Test Date	2020/03/19
Channel number	CH High	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	73.65	41.97	-8.58	33.39	40.00	-6.61	Peak	VERTICAL
2	119.24	40.74	-7.81	32.93	43.50	-10.57	Peak	VERTICAL
3	336.52	44.30	-3.08	41.22	46.00	-4.78	Peak	VERTICAL
4	369.50	36.42	-2.56	33.86	46.00	-12.14	Peak	VERTICAL
5	480.08	34.51	-0.85	33.66	46.00	-12.34	Peak	VERTICAL
6	666.32	34.43	2.20	36.63	46.00	-9.37	Peak	VERTICAL
1	73.65	44.92	-8.58	36.34	40.00	-3.66	Peak	HORIZONTAL
2	167.74	39.63	-5.00	34.63	43.50	-8.87	Peak	HORIZONTAL
3	336.52	42.89	-3.08	39.81	46.00	-6.19	Peak	HORIZONTAL
4	517.91	36.11	-0.27	35.84	46.00	-10.16	Peak	HORIZONTAL
5	640.13	33.33	1.92	35.25	46.00	-10.75	Peak	HORIZONTAL
6	817.64	31.55	4.85	36.40	46.00	-9.60	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9kHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode	802.11n HT40 TX mode	Test Date	2020/03/19
Channel number	CH Low	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	119.24	41.60	-7.81	33.79	43.50	-9.71	Peak	VERTICAL
2	175.50	36.32	-5.69	30.63	43.50	-12.87	Peak	VERTICAL
3	323.91	41.69	-3.46	38.23	46.00	-7.77	Peak	VERTICAL
4	455.83	34.44	-1.06	33.38	46.00	-12.62	Peak	VERTICAL
5	668.26	35.89	2.21	38.10	46.00	-7.90	Peak	VERTICAL
6	815.70	31.41	4.76	36.17	46.00	-9.83	Peak	VERTICAL
1	73.65	45.65	-8.58	37.07	40.00	-2.93	Peak	HORIZONTAL
2	174.53	39.28	-5.59	33.69	43.50	-9.81	Peak	HORIZONTAL
3	348.16	43.44	-2.98	40.46	46.00	-5.54	Peak	HORIZONTAL
4	519.85	35.88	-0.19	35.69	46.00	-10.31	Peak	HORIZONTAL
5	591.63	32.54	1.21	33.75	46.00	-12.25	Peak	HORIZONTAL
6	742.95	32.27	3.76	36.03	46.00	-9.97	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9kHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode	802.11n HT40 TX mode	Test Date	2020/03/19
Channel number	CH Mid	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	73.65	43.69	-8.58	35.11	40.00	-4.89	Peak	VERTICAL
2	119.24	41.18	-7.81	33.37	43.50	-10.13	Peak	VERTICAL
3	334.58	40.75	-3.08	37.67	46.00	-8.33	Peak	VERTICAL
4	480.08	35.01	-0.85	34.16	46.00	-11.84	Peak	VERTICAL
5	519.85	34.55	-0.19	34.36	46.00	-11.64	Peak	VERTICAL
6	666.32	34.90	2.20	37.10	46.00	-8.90	Peak	VERTICAL
1	73.65	47.62	-8.58	39.04	40.00	-0.96	Peak	HORIZONTAL
2	173.56	39.85	-5.47	34.38	43.50	-9.12	Peak	HORIZONTAL
3	312.27	45.62	-3.70	41.92	46.00	-4.08	Peak	HORIZONTAL
4	369.50	38.16	-2.56	35.60	46.00	-10.40	Peak	HORIZONTAL
5	480.08	35.66	-0.85	34.81	46.00	-11.19	Peak	HORIZONTAL
6	640.13	32.50	1.92	34.42	46.00	-11.58	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9kHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode	802.11n HT40 TX mode	Test Date	2020/03/19
Channel number	CH High	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	119.24	41.62	-7.81	33.81	43.50	-9.69	Peak	VERTICAL
2	239.52	38.09	-5.98	32.11	46.00	-13.89	Peak	VERTICAL
3	332.64	38.93	-3.11	35.82	46.00	-10.18	Peak	VERTICAL
4	480.08	34.30	-0.85	33.45	46.00	-12.55	Peak	VERTICAL
5	666.32	34.56	2.20	36.76	46.00	-9.24	Peak	VERTICAL
6	813.76	31.54	4.70	36.24	46.00	-9.76	Peak	VERTICAL
1	73.65	46.91	-8.58	38.33	40.00	-1.67	Peak	HORIZONTAL
2	173.56	38.52	-5.47	33.05	43.50	-10.45	Peak	HORIZONTAL
3	335.55	42.50	-3.07	39.43	46.00	-6.57	Peak	HORIZONTAL
4	394.72	35.97	-2.16	33.81	46.00	-12.19	Peak	HORIZONTAL
5	519.85	35.95	-0.19	35.76	46.00	-10.24	Peak	HORIZONTAL
6	640.13	32.87	1.92	34.79	46.00	-11.21	Peak	HORIZONTAL

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9kHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Dipole Antenna

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode	801.11b TX mode	Test Date	2020/03/19
Channel number	CH Low	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4824.00	49.98	-9.17	40.81	54.00	-13.19	Average	VERTICAL
2	4824.00	63.03	-9.17	53.86	74.00	-20.14	Peak	VERTICAL
3	7062.00	46.90	-2.42	44.48	74.00	-29.52	Peak	VERTICAL
1	4824.00	48.31	-9.17	39.14	54.00	-14.86	Average	HORIZONTAL
2	4824.00	63.08	-9.17	53.91	74.00	-20.09	Peak	HORIZONTAL
3	7027.00	47.90	-2.62	45.28	74.00	-28.72	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode	802.11b TX mode	Test Date	2020/03/19
Channel number	CH Mid	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4874.00	58.02	-9.04	48.98	74.00	-25.02	Peak	VERTICAL
2	6901.00	46.98	-3.23	43.75	74.00	-30.25	Peak	VERTICAL
1	4874.00	59.88	-9.04	50.84	74.00	-23.16	Peak	HORIZONTAL
2	7405.00	46.84	-1.57	45.27	74.00	-28.73	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode	802.11b TX mode	Test Date	2020/03/19
Channel number	CH High	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4924.00	62.52	-8.91	53.61	74.00	-20.39	Peak	VERTICAL
2	7034.00	46.93	-2.58	44.35	74.00	-29.65	Peak	VERTICAL
1	4924.00	60.41	-8.91	51.50	74.00	-22.50	Peak	HORIZONTAL
2	7251.00	46.07	-1.64	44.43	74.00	-29.57	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode	801.11g TX mode	Test Date	2020/03/19
Channel number	CH Low	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4824.00	62.20	-9.17	53.03	74.00	-20.97	Peak	VERTICAL
2	7013.00	47.02	-2.69	44.33	74.00	-29.67	Peak	VERTICAL
1	4824.00	61.89	-9.17	52.72	74.00	-21.28	Peak	HORIZONTAL
2	7055.00	46.96	-2.47	44.49	74.00	-29.51	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode	802.1g TX mode	Test Date	2020/03/19
Channel number	CH Mid	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4874.00	59.58	-9.04	50.54	74.00	-23.46	Peak	VERTICAL
2	7027.00	46.89	-2.62	44.27	74.00	-29.73	Peak	VERTICAL
1	4874.00	60.03	-9.04	50.99	74.00	-23.01	Peak	HORIZONTAL
2	7083.00	46.94	-2.31	44.63	74.00	-29.37	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode	802.11g TX mode	Test Date	2020/03/19
Channel number	CH High	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4924.00	61.25	-8.91	52.34	74.00	-21.66	Peak	VERTICAL
2	7405.00	48.43	-1.57	46.86	74.00	-27.14	Peak	VERTICAL
1	4924.00	60.95	-8.91	52.04	74.00	-21.96	Peak	HORIZONTAL
2	7384.00	46.46	-1.57	44.89	74.00	-29.11	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode	802.11n HT20 TX mode	Test Date	2020/03/19
Channel number	CH Low	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4924.00	62.18	-8.91	53.27	74.00	-20.73	Peak	VERTICAL
2	7020.00	47.16	-2.66	44.50	74.00	-29.50	Peak	VERTICAL
1	3282.00	56.46	-14.54	41.92	74.00	-32.08	Peak	HORIZONTAL
2	4924.00	61.47	-8.91	52.56	74.00	-21.44	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode	802.11n HT20 TX mode	Test Date	2020/03/19
Channel number	CH Mid	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4874.00	58.74	-9.04	49.70	74.00	-24.30	Peak	VERTICAL
2	7363.00	46.84	-1.58	45.26	74.00	-28.74	Peak	VERTICAL
1	4874.00	59.02	-9.04	49.98	74.00	-24.02	Peak	HORIZONTAL
2	7384.00	46.53	-1.57	44.96	74.00	-29.04	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode	802.11n HT20 TX mode	Test Date	2020/03/19
Channel number	CH High	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4924.00	62.32	-8.91	53.41	74.00	-20.59	Peak	VERTICAL
2	7412.00	48.03	-1.57	46.46	74.00	-27.54	Peak	VERTICAL
1	3282.00	55.59	-14.54	41.05	74.00	-32.95	Peak	HORIZONTAL
2	4924.00	60.33	-8.91	51.42	74.00	-22.58	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode	802.11n HT40 TX mode	Test Date	2020/03/19
Channel number	CH Low	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4844.00	57.30	-9.12	48.18	74.00	-25.82	Peak	VERTICAL
2	7482.00	47.97	-1.62	46.35	74.00	-27.65	Peak	VERTICAL
1	3226.00	56.17	-14.38	41.79	74.00	-32.21	Peak	HORIZONTAL
2	4844.00	57.31	-9.12	48.19	74.00	-25.81	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode	802.11n HT40 TX mode	Test Date	2020/03/19
Channel number	CH Mid	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	3247.00	52.23	-14.45	37.78	74.00	-36.22	Peak	VERTICAL
2	4874.00	55.64	-9.04	46.60	74.00	-27.40	Peak	VERTICAL
1	3247.00	56.00	-14.45	41.55	74.00	-32.45	Peak	HORIZONTAL
2	4874.00	55.77	-9.04	46.73	74.00	-27.27	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode	802.11n HT40 TX mode	Test Date	2020/03/19
Channel number	CH High	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4904.00	55.72	-8.95	46.77	74.00	-27.23	Peak	VERTICAL
2	7279.00	46.96	-1.63	45.33	74.00	-28.67	Peak	VERTICAL
1	3268.00	57.07	-14.50	42.57	74.00	-31.43	Peak	HORIZONTAL
2	4904.00	57.14	-8.95	48.19	74.00	-25.81	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

PCB Antenna

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode	801.11b TX mode	Test Date	2020/03/19
Channel number	CH Low	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	3212.00	63.16	-14.36	48.80	74.00	-25.20	Peak	VERTICAL
2	4824.00	51.76	-9.17	42.59	54.00	-11.41	Average	VERTICAL
3	4824.00	66.55	-9.17	57.38	74.00	-16.62	Peak	VERTICAL
1	3212.00	63.16	-14.36	48.80	74.00	-25.20	Peak	HORIZONTAL
2	4824.00	51.76	-9.17	42.59	54.00	-11.41	Average	HORIZONTAL
3	4824.00	66.55	-9.17	57.38	74.00	-16.62	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode	802.11b TX mode	Test Date	2020/03/19
Channel number	CH Mid	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	3247.00	68.82	-14.45	54.37	74.00	-19.63	Peak	VERTICAL
2	4874.00	51.29	-9.04	42.25	54.00	-11.75	Average	VERTICAL
3	4874.00	66.05	-9.04	57.01	74.00	-16.99	Peak	VERTICAL
1	3247.00	64.41	-14.45	49.96	74.00	-24.04	Peak	HORIZONTAL
2	4874.00	54.83	-9.04	45.79	54.00	-8.21	Average	HORIZONTAL
3	4874.00	69.22	-9.04	60.18	74.00	-13.82	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode	802.11b TX mode	Test Date	2020/03/19
Channel number	CH High	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	3282.00	68.81	-14.54	54.27	74.00	-19.73	Peak	VERTICAL
2	4924.00	50.13	-8.91	41.22	54.00	-12.78	Average	VERTICAL
3	4924.00	65.56	-8.91	56.65	74.00	-17.35	Peak	VERTICAL
1	3282.00	65.33	-14.54	50.79	74.00	-23.21	Peak	HORIZONTAL
2	4924.00	51.33	-8.91	42.42	54.00	-11.58	Average	HORIZONTAL
3	4924.00	66.38	-8.91	57.47	74.00	-16.53	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode	801.11g TX mode	Test Date	2020/03/19
Channel number	CH Low	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	3212.00	69.19	-14.36	54.83	74.00	-19.17	Peak	VERTICAL
2	4824.00	50.98	-9.17	41.81	54.00	-12.19	Average	VERTICAL
3	4824.00	65.62	-9.17	56.45	74.00	-17.55	Peak	VERTICAL
1	3212.00	64.45	-14.36	50.09	74.00	-23.91	Peak	HORIZONTAL
2	4824.00	62.55	-9.17	53.38	74.00	-20.62	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode	802.1g TX mode	Test Date	2020/03/19
Channel number	CH Mid	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	3247.00	68.84	-14.45	54.39	74.00	-19.61	Peak	VERTICAL
2	4874.00	50.83	-9.04	41.79	54.00	-12.21	Average	VERTICAL
3	4874.00	65.89	-9.04	56.85	74.00	-17.15	Peak	VERTICAL
1	3247.00	64.51	-14.45	50.06	74.00	-23.94	Peak	HORIZONTAL
2	4874.00	54.91	-9.04	45.87	54.00	-8.13	Average	HORIZONTAL
3	4874.00	69.17	-9.04	60.13	74.00	-13.87	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode	802.11g TX mode	Test Date	2020/03/19
Channel number	CH High	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	3282.00	68.74	-14.54	54.20	74.00	-19.80	Peak	VERTICAL
2	4924.00	50.73	-8.91	41.82	54.00	-12.18	Average	VERTICAL
3	4924.00	65.08	-8.91	56.17	74.00	-17.83	Peak	VERTICAL
1	3282.00	65.44	-14.54	50.90	74.00	-23.10	Peak	HORIZONTAL
2	4924.00	53.91	-8.91	45.00	54.00	-9.00	Average	HORIZONTAL
3	4924.00	67.13	-8.91	58.22	74.00	-15.78	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode	802.11n HT20 TX mode	Test Date	2020/03/19
Channel number	CH Low	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	3212.00	65.25	-14.36	50.89	74.00	-23.11	Peak	VERTICAL
2	4824.00	50.41	-9.17	41.24	54.00	-12.76	Average	VERTICAL
3	4824.00	65.42	-9.17	56.25	74.00	-17.75	Peak	VERTICAL
1	3212.00	64.36	-14.36	50.00	74.00	-24.00	Peak	HORIZONTAL
2	4824.00	50.93	-9.17	41.76	54.00	-12.24	Average	HORIZONTAL
3	4824.00	64.34	-9.17	55.17	74.00	-18.83	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode	802.11n HT20 TX mode	Test Date	2020/03/19
Channel number	CH Mid	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	3247.00	67.05	-14.45	52.60	74.00	-21.40	Peak	VERTICAL
2	4874.00	52.27	-9.04	43.23	54.00	-10.77	Average	VERTICAL
3	4874.00	66.63	-9.04	57.59	74.00	-16.41	Peak	VERTICAL
1	3247.00	64.67	-14.45	50.22	74.00	-23.78	Peak	HORIZONTAL
2	4874.00	53.84	-9.04	44.80	54.00	-9.20	Average	HORIZONTAL
3	4874.00	68.62	-9.04	59.58	74.00	-14.42	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode	802.11n HT20 TX mode	Test Date	2020/03/19
Channel number	CH High	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	3282.00	67.55	-14.54	53.01	74.00	-20.99	Peak	VERTICAL
2	4924.00	50.51	-8.91	41.60	54.00	-12.40	Average	VERTICAL
3	4924.00	65.68	-8.91	56.77	74.00	-17.23	Peak	VERTICAL
1	3282.00	65.16	-14.54	50.62	74.00	-23.38	Peak	HORIZONTAL
2	4924.00	52.18	-8.91	43.27	54.00	-10.73	Average	HORIZONTAL
3	4924.00	66.72	-8.91	57.81	74.00	-16.19	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode	802.11n HT40 TX mode	Test Date	2020/03/19
Channel number	CH Low	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	3226.00	52.56	-14.38	38.18	74.00	-35.82	Peak	VERTICAL
2	4844.00	57.07	-9.12	47.95	74.00	-26.05	Peak	VERTICAL
1	3226.00	55.29	-14.38	40.91	74.00	-33.09	Peak	HORIZONTAL
2	4844.00	59.87	-9.12	50.75	74.00	-23.25	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode	802.11n HT40 TX mode	Test Date	2020/03/19
Channel number	CH Mid	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	3247.00	51.82	-14.45	37.37	74.00	-36.63	Peak	VERTICAL
2	4874.00	52.05	-9.04	43.01	74.00	-30.99	Peak	VERTICAL
1	3247.00	54.40	-14.45	39.95	74.00	-34.05	Peak	HORIZONTAL
2	4874.00	55.36	-9.04	46.32	74.00	-27.68	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode	802.11n HT40 TX mode	Test Date	2020/03/19
Channel number	CH High	Test By	Weitin
Temperature	25 °C	Pol	Ver./Hor
Humidity	60 %		

No	Freq MHz	Reading dBuV	Factor dB	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	3268.00	52.39	-14.50	37.89	74.00	-36.11	Peak	VERTICAL
2	4904.00	51.26	-8.95	42.31	74.00	-31.69	Peak	VERTICAL
1	3268.00	54.71	-14.50	40.21	74.00	-33.79	Peak	HORIZONTAL
2	4904.00	55.09	-8.95	46.14	74.00	-27.86	Peak	HORIZONTAL

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

9 100kHz Bandwidth of Band Edges Measurement

9.1 Standard Applicable:

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

According to RSS-247 issue 2, §5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

9.2 Measurement Equipment Used:

9.2.1. Conducted Emission at antenna port:

Refer to section 6.2 for details.


9.2.2. Radiated emission:

Location	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Conducted	Spectrum analyzer	R&S	FSP40	100116	01/10/2020	01/10/2021
Chamber 19	EMI Receiver	R&S	ESR3	102461	08/08/2018	08/08/2020
Chamber 19	Loop Antenna	EM	EM-6879	271	05/31/2019	05/31/2020
Chamber 19	Bilog Antenna (30MHz-1GHz)	Schwarzbeck	VULB9168 w 5dB Att.	736	02/11/2020	02/11/2021
Chamber 19	Horn antenna (1GHz-18GHz)	Schwarzbeck	9120D	9120D-1627	06/17/2019	06/17/2020
Chamber 19	Horn antenna (18GHz-26GHz)	Com-power	AH-826	081001	11/25/2019	11/25/2020
Chamber 19	Horn antenna (26GHz-40GHz)	Com-power	AH-640	100A	03/13/2020	03/13/2021
Chamber 19	Preamplifier (9kHz-1GHz)	HP	8447F	3113A06362	01/06/2020	01/06/2021
Chamber 19	Preamplifier (1GHz-26GHz)	Agilent	8449B	3008A02471	10/05/2019	10/05/2020
Chamber 19	Preamplifier (26GHz-40GHz)	MITEQ	JS4-26004000- 27-5A	818471	05/06/2019	05/06/2020
Chamber 19	RF Cable (9kHz-18GHz)	HUBER SU- HNER	Sucoflex 104A	MY1397/4A	01/10/2020	01/10/2021
Chamber 19	RF Cable (18GHz-40GHz)	HUBER SU- HNER	Sucoflex 102	27963/2&374 21/2	11/21/2019	11/21/2020
Chamber 19	Signal Generator	Anritsu	MG3692A	20311	01/06/2020	01/06/2021
Chamber 19	Test Software	Audix	E3 Ver:6.12023	N/A	N/A	N/A


9.3 Test Setup

The test item only performed radiated mode

(A) Radiated Emission Test Setup for frequency below 1000MHz



(B) Radiated Emission Test Setup for frequency above 1 GHz



9.4 Measurement Procedure:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = operating frequency.
4. Set the spectrum analyzer as RBW, VBW=100kHz, Span=25MHz, Sweep = auto
5. Mark Peak, 2.390GHz and 2.4835GHz and record the max. level.
6. Repeat above procedures until all frequency measured were complete.

9.5 Field Strength Calculation:

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where	FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
	RA = Reading Amplitude	AG = Amplifier Gain
	AF = Antenna Factor	

9.6 Measurement Result:


Note: Refer to next page spectrum analyzer data chart and tabular data sheets.

Dipole Ant

Radiated Emission: 802.11 b mode


Operation Mode TX CH Low
Fundamental Frequency 2412 MHz
Temperature 25 °C

Test Date 2020/03/19
Test By Weitin
Humidity 60 %



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2390.00	15.81	32.73	48.54	54.00	-5.46	Average	VERTICAL
2	2390.00	25.81	32.73	58.54	74.00	-15.46	Peak	VERTICAL
3	2400.00	30.66	32.72	63.38	80.45	-17.07	Peak	VERTICAL
4	2411.70	67.71	32.74	100.45	F	--	Peak	VERTICAL

Remark: F'' denotes fundamental frequency




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2390.00	18.74	32.73	51.47	54.00	-2.53	Average	HORIZONTAL
2	2390.00	28.68	32.73	61.41	74.00	-12.59	Peak	HORIZONTAL
3	2400.00	37.30	32.72	70.02	88.90	-18.88	Peak	HORIZONTAL
4	2411.70	76.16	32.74	108.90	F	--	Peak	HORIZONTAL

Remark: F” denotes fundamental frequency


Operation Mode TX CH High
Fundamental Frequency 2462 MHz
Temperature 25 °C

Test Date 2020/03/19
Test By Weitin
Humidity 60 %



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2459.54	69.73	32.77	102.50	F	---	Peak	VERTICAL
2	2483.50	17.41	32.78	50.19	54.00	-3.81	Average	VERTICAL
3	2483.50	27.63	32.78	60.41	74.00	-13.59	Peak	VERTICAL

Remark: "F" denotes fundamental frequency




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2461.65	78.00	32.77	110.77	F	---	Peak	HORIZONTAL
2	2483.50	17.09	32.78	49.87	54.00	-4.13	Average	HORIZONTAL
3	2483.50	27.07	32.78	59.85	74.00	-14.15	Peak	HORIZONTAL

Remark: "F" denotes fundamental frequency

Radiated Emission: 802.11 g mode


Operation Mode TX CH Low
Fundamental Frequency 2412 MHz
Temperature 25 °C

Test Date 2020/03/19
Test By Weitin
Humidity 60 %



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2390.00	17.49	32.73	50.22	54.00	-3.78	Average	VERTICAL
2	2390.00	27.21	32.73	59.94	74.00	-14.06	Peak	VERTICAL
3	2400.00	31.67	32.72	64.39	80.37	-15.98	Peak	VERTICAL
4	2418.19	67.64	32.73	100.37	F	---	Peak	VERTICAL

Remark: "F" denotes fundamental frequency




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2390.00	16.98	32.73	49.71	54.00	-4.29	Average	HORIZONTAL
2	2390.00	26.82	32.73	59.55	74.00	-14.45	Peak	HORIZONTAL
3	2400.00	34.21	32.72	66.93	85.81	-18.88	Peak	HORIZONTAL
4	2414.38	73.08	32.73	105.81	F	---	Peak	HORIZONTAL

Remark: "F" denotes fundamental frequency


Operation Mode TX CH High
Fundamental Frequency 2462 MHz
Temperature 25 °C

Test Date 2020/03/19
Test By Weitin
Humidity 60 %



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2457.18	64.80	32.77	97.57	F	---	Peak	VERTICAL
2	2483.50	17.18	32.78	49.96	54.00	-4.04	Average	VERTICAL
3	2483.50	27.05	32.78	59.83	74.00	-14.17	Peak	VERTICAL

Remark: "F" denotes fundamental frequency




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2458.24	72.55	32.77	105.32	F	---	Peak	HORIZONTAL
2	2483.50	19.33	32.78	52.11	54.00	-1.89	Average	HORIZONTAL
3	2483.50	29.14	32.78	61.92	74.00	-12.08	Peak	HORIZONTAL

Remark: "F" denotes fundamental frequency

Radiated Emission: 802.11 n_HT20 mode


Operation Mode TX CH Low
Fundamental Frequency 2412 MHz
Temperature 25 °C

Test Date 2020/03/19
Test By Weitin
Humidity 60 %



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2390.00	17.31	32.73	50.04	54.00	-3.96	Average	VERTICAL
2	2390.00	27.29	32.73	60.02	74.00	-13.98	Peak	VERTICAL
3	2400.00	31.16	32.72	63.88	80.16	-16.28	Peak	VERTICAL
4	2416.85	67.43	32.73	100.16	F	---	Peak	VERTICAL

Remark: "F" denotes fundamental frequency




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2390.00	16.48	32.73	49.21	54.00	-4.79	Average	HORIZONTAL
2	2390.00	26.33	32.73	59.06	74.00	-14.94	Peak	HORIZONTAL
3	2400.00	34.71	32.72	67.43	85.58	-18.15	Peak	HORIZONTAL
4	2419.09	72.85	32.73	105.58	F	---	Peak	HORIZONTAL

Remark: "F" denotes fundamental frequency


Operation Mode TX CH High
Fundamental Frequency 2462 MHz
Temperature 25 °C

Test Date 2020/03/19
Test By Weitin
Humidity 60 %



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2458.00	64.66	32.77	97.43	F	---	Peak	VERTICAL
2	2483.50	17.48	32.78	50.26	54.00	-3.74	Average	VERTICAL
3	2483.50	27.02	32.78	59.80	74.00	-14.20	Peak	VERTICAL

Remark: "F" denotes fundamental frequency




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2460.98	72.56	32.77	105.33	F	---	Peak	HORIZONTAL
2	2483.50	18.31	32.78	51.09	54.00	-2.91	Average	HORIZONTAL
3	2483.50	28.05	32.78	60.83	74.00	-13.17	Peak	HORIZONTAL

Remark: "F" denotes fundamental frequency

Radiated Emission: 802.11 n_HT40 mode


Operation Mode TX CH Low
Fundamental Frequency 2412 MHz
Temperature 25 °C

Test Date 2020/03/19
Test By Weitin
Humidity 60 %



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2390.00	16.00	32.73	48.73	54.00	-5.27	Average	VERTICAL
2	2390.00	25.88	32.73	58.61	74.00	-15.39	Peak	VERTICAL
3	2400.00	34.28	32.72	67.00	77.58	-10.58	Peak	VERTICAL
4	2431.04	64.83	32.75	97.58	F	---	Peak	VERTICAL

Remark: "F" denotes fundamental frequency




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2390.00	16.77	32.73	49.50	54.00	-4.50	Average	HORIZONTAL
2	2390.00	26.63	32.73	59.36	74.00	-14.64	Peak	HORIZONTAL
3	2400.00	38.03	32.72	70.75	83.28	-12.53	Peak	HORIZONTAL
4	2432.36	70.53	32.75	103.28	F	---	Peak	HORIZONTAL

Remark: "F" denotes fundamental frequency


Operation Mode TX CH High
Fundamental Frequency 2462 MHz
Temperature 25 °C

Test Date 2020/03/19
Test By Weitin
Humidity 60 %



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2437.64	62.51	32.74	95.25	F	---	Peak	VERTICAL
2	2483.50	17.62	32.78	50.40	54.00	-3.60	Average	VERTICAL
3	2483.50	27.43	32.78	60.21	74.00	-13.79	Peak	VERTICAL

Remark: "F" denotes fundamental frequency




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2443.42	70.91	32.75	103.66	F	---	Peak	HORIZONTAL
2	2483.50	20.93	32.78	53.71	54.00	-0.29	Average	HORIZONTAL
3	2483.50	30.87	32.78	63.65	74.00	-10.35	Peak	HORIZONTAL

Remark: "F" denotes fundamental frequency

Radiated Emission: BLE mode


Operation Mode TX CH Low
Fundamental Frequency 2402 MHz
Temperature 25 °C

Test Date 2020/03/19
Test By Weitin
Humidity 60 %



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2390.00	49.08	-2.98	46.10	74.00	-27.90	Peak	VERTICAL
2	2400.00	83.27	-2.99	80.28	82.47	-2.19	Peak	VERTICAL
3	2402.35	105.46	-2.99	102.47	F	--	Peak	VERTICAL

Remark: "F" denotes fundamental frequency




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2390.00	48.27	-2.98	45.29	74.00	-28.71	Peak	HORIZONTAL
2	2400.00	78.57	-2.99	75.58	77.82	-2.24	Peak	HORIZONTAL
3	2402.35	100.81	-2.99	97.82	F	--	Peak	HORIZONTAL

Remark: "F" denotes fundamental frequency


Operation Mode TX CH High
Fundamental Frequency 2480 MHz
Temperature 25 °C

Test Date 2020/03/19
Test By Weitin
Humidity 60 %



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2479.76	106.78	-3.07	103.71	F	--	Peak	VERTICAL
2	2483.50	50.67	-2.94	47.73	54.00	-6.27	Average	VERTICAL
3	2483.50	68.51	-2.94	65.57	74.00	-8.43	Peak	VERTICAL

Remark: "F" denotes fundamental frequency



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2479.78	102.01	-3.07	98.94	F	--	Peak	HORIZONTAL
2	2483.49	47.61	-2.94	44.67	54.00	-9.33	Average	HORIZONTAL
3	2483.49	64.08	-2.94	61.14	74.00	-12.86	Peak	HORIZONTAL

Remark: "F" denotes fundamental frequency

10 Peak Power Spectral Density

10.1 Standard Applicable:

According to §15.247(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

According to RSS-247 issue 2, §5.2

(2)The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of Section 5.4(d), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

10.2 Measurement Equipment Used:

Refer to section 6.2 for details.

10.3 Test Set-up:

Refer to section 7.3 for details.

10.4 Measurement Procedure:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW =3kHz, VBW = 10kHz, Set the span to 1.5 DTS bandwidth., Sweep=Auto
4. Record the max. reading.
5. Repeat above procedures until all frequency measured were complete.

10.5 Measurement Result:

802.11b Mode

CH	Power Density Level dBm/3kHz	Maximum Limit (dBm)
Low	-7.03	8
Mid	-8.25	8
High	-9.43	8

802.11g Mode

CH	Power Density Level dBm/3kHz	Maximum Limit (dBm)
Low	-15.15	8
Mid	-16.07	8
High	-16.73	8

802.11n HT20

CH	Power Density Level dBm/3kHz	Maximum Limit (dBm)
Low	-14.89	8
Mid	-16.09	8
High	-16.82	8

802.11n HT40

CH	Power Density Level dBm/3kHz	Maximum Limit (dBm)
Low	-17.49	8
Mid	-18.82	8
High	-19.13	8

802.11b


Power Spectral Density Test Plot (CH-Low)



Power Spectral Density Test Plot (CH-Mid)




Power Spectral Density Test Plot (CH-High)




802.11g


Power Spectral Density Test Plot (CH-Low)



Power Spectral Density Test Plot (CH-Mid)




Power Spectral Density Test Plot (CH-High)




802.11n_HT20


Power Spectral Density Test Plot (CH-Low)



Power Spectral Density Test Plot (CH-Mid)




Power Spectral Density Test Plot (CH-High)




802.11n_HT40


Power Spectral Density Test Plot (CH-Low)



Power Spectral Density Test Plot (CH-Mid)



Power Spectral Density Test Plot (CH-High)



11 Antenna Requirement

11.1 Standard Applicable:

According to §15.203, Antenna requirement.

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

According to RSS-GEN 6.8 antenna requirement:

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna.

The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below). When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

11.2 Antenna Connected Construction:

The directional gains of antenna used for transmitting is below table, and the antenna connector is designed with unique type RF connector and no consideration of replacement. Please see EUT photo and antenna spec. for details.



Antenna Designation:



	Type	Part No.	Gain (2.4GHz)
Ant 1	PCB Antenna	ESP32M	2.22dBi
Ant 2	PCB Antenna	ESP32F	1.70dBi
Ant 3	Dipole Antneea	ESP32E	0dBi

APPENDIX 1


PHOTOGRAPHS OF SET UP



Radiated Emission Setup Photos Dipole Antenna





Radiated Emission Setup Photos Dipole Antenna






Conducted Emission Setup Photos




APPENDIX 2

PHOTOGRAPHS OF EUT


EUT 1 ESP32




EUT 2 ESP32




EUT 3 ESP32



EUT 4 ESP32E




EUT 5 ESP32E




EUT 6 ESP32E




EUT 7 ESP32F




EUT 8 ESP32F




EUT 9 ESP32F




EUT 10




EUT 11




EUT 12




EUT 13



EUT 14




EUT 15 ESP32



EUT 16 ESP32E



EUT 17 ESP32F



~ End of Report ~